

DESCRIPTION

A full bodied bituminous aluminium coating suitable for the protection of properly prepared steel, asphalt and bituminous substrates.

RECOMMENDED USES

Ideal for roofs.



SPECIAL PROPERTIES

Solar reflective. Quick drying. Reduces the heat build up in rooms below.

COLOUR RANGE

Metallic Silver.

FINISH

Metallic lustre.

VOLUME SOLID

47%

COVERAGE



Johnstone's Solar Reflective Paint will cover at the rate of approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 4–6 hours.
Recoat after 16–24 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

CLEANER

White Spirit.

VOC CONTENT

HIGH VOC CONTENT 25–50%.

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i): 600g/l (2007) / 500g/l (2010).
This product contains max 500g/l VOC.

FILM THICKNESS

Wet: 53µm, dry: 25µm.

SIZE

5 Litre.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose, flaking material, dirt and grease. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354100.

APPLICATION



Easy to apply by brush. A minimum of 2 coats are recommended.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- PAINT UN1263.
- Contains Bitumen & White Spirit.
- HARMFUL; POSSIBLE RISK OF IRREVERSIBLE EFFECTS IN CONTACT WITH SKIN.
- DANGEROUS FOR THE ENVIRONMENT.
- Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment.
- Avoid release to the environment.
- FLAMMABLE.
- Keep away from sources of ignition – No smoking.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – DO NOT USE SOLVENT OR THINNERS.
- Wear suitable protective clothing and gloves.
- Ensure maximum ventilation during application and drying.
- When applying to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air fed respiratory protective equipment.
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

