

## DESCRIPTION

A single pack, rust inhibiting primer for use on iron and steel. Suitable as a primer for many paint systems, as a finish coat in its own right and also for repairing galvanised steel. Prevents spread of corrosion beneath the paint film resulting from scratches and chips.

## RECOMMENDED USES



Primes iron, steel, galvanised steel and ferrous metal substrates.

## SPECIAL PROPERTIES

Prevents spread of corrosion beneath paint film resulting from scratches and chips.

## COLOUR RANGE

Grey.

## FINISH

Matt.

## VOLUME SOLID

40%.

## COVERAGE



Johnstone's High Build Zinc Rich Primer will cover at the rate of approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

## DRYING TIME



Touch dry in 4–6 hours.  
Recoat after 16–24 hours.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

## CLEANER

TC4 Thinner and Cleaner.

## VOC CONTENT

HIGH VOC CONTENT 25-50%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/I): 600g/l (2007) / 500g/l (2010). This product contains max 500g/l VOC.

## FILM THICKNESS

Wet: 100µm, dry: 40µm.

## SIZE

1 Litre, 2.5 Litre and 5 Litre.

## PREPARATION

Grit blast steel to SIS-Sa 2½. Wire brush galvanised steel to remove corrosion and degrease with Johnstone's Cleaner and Degreaser. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354100.

## APPLICATION



Stir thoroughly before use. Suitable for application by brush or roller.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with TC4 Thinner and Cleaner. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- PAINT UN1263
- FLAMMABLE.
- Contains Zinc Powder.
- DANGEROUS FOR THE ENVIRONMENT.
- Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment.
- Avoid release to the environment.
- Contains Cobalt Carboxylate and Ethyl Methyl Ketoxime. May produce an allergic reaction.
- Keep away from sources of ignition – No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – **DO NOT USE SOLVENT OR THINNERS.**
- When applying to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air fed respiratory protective equipment.
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

## PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

