

DESCRIPTION

A solvent-borne, protective metallic finish formulated for use on suitably prepared metal surfaces such as storage tanks, ducting and pipework. Based on an oil varnish medium and aluminium flake it will withstand temperatures up to 150°C. It also benefits from solar reflective properties.

RECOMMENDED USES



Exterior of storage tanks, ducting and pipework. Avoid areas that are consistently handled to prevent the transfer of aluminium.

SPECIAL PROPERTIES

Heat resistant up to 150°C. Solar reflective properties.

COLOUR RANGE

Silver.

FINISH

Metallic.

VOLUME SOLID

37%

COVERAGE



Johnstone's Aluminium Paint will cover at the rate of approximately 14–16 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 4–6 hours.
Recoat after 16–24 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

CLEANER

White Spirit.

VOC CONTENT

HIGH VOC CONTENT 25-50%.
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 400g/l (2007).
This product contains max 400g/l VOC.

FILM THICKNESS

Wet: 78µm, dry: 28µm.

SIZE

2.5 Litre and 5 Litre.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Any rust should be removed by wire brushing. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding. Prime bare surfaces with the appropriate Johnstone's Primer. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354100.

APPLICATION



Stir well. Easy to apply by brush or roller.
Do not apply over polystyrene surfaces.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- PAINT UN1263.
- Contains White Spirit.
- DANGEROUS FOR THE ENVIRONMENT.
- Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment.
- May produce an allergic reaction.
- Contains Cobalt Carboxylate and Ethyl Methyl Ketoxime.
- FLAMMABLE.
- Keep away from sources of ignition – No smoking.
- Repeated exposure may cause skin dryness or cracking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – **DO NOT USE SOLVENT OR THINNERS.**
- Restrict interior use to small surface areas.
Not recommended for interior use on large surface areas or in confined spaces.
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

