

4.5

Matt Blackboard Paint

DESCRIPTION

An attractive smooth, non-reflective black finish formulated for interior use.

RECOMMENDED USES



Beams, panelling, doors, decorative ironwork, stage scenery and blackboards.

SPECIAL PROPERTIES

Non-reflective, washable.

COLOUR RANGE

Black.

FINISH

Matt.

VOLUME SOLID

52%.

COVERAGE



Johnstone's Matt Blackboard Paint will cover at the rate of approximately 20 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 2–3 hours.
Recoat after 16–24 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

White Spirit.

VOC CONTENT

HIGH VOC CONTENT 25–50%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 400g/l (2007).
This product contains max 400g/l VOC.

FILM THICKNESS

Wet: 50µm, dry: 25µm.

SIZE

1 Litre and 2.5 Litre.

PREPARATION

All surfaces to be painted should be sound, clean, dry and free from loose and flaking material. Previously painted surfaces should be rubbed down with fine waterproof abrasive paper to provide a key. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding. Prime bare surfaces with the appropriate Johnstone's Primer. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354100.

APPLICATION



Stir well. Easy to apply by brush.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- PAINT PRODUCT.
- FLAMMABLE.
- Contains Cobalt Carboxylate and Ethyl Methyl Ketoxime. May produce an allergic reaction.
- Keep away from sources of ignition – No smoking.
- Repeated exposure may cause skin dryness or cracking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – **DO NOT USE SOLVENT OR THINNERS.**
- Restrict interior use to small surface areas. Not recommended for interior use on large surface areas.
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.



SigmaKalon DECORATIVE COATINGS UK AND IRELAND, SIGMAKALON UK LIMITED

Huddersfield Road, Birstall, Batley, West Yorkshire WF17 9XA Telephone: 01924 354000 Facsimile: 01924 354001 www.johnstones-paints.co.uk