

DESCRIPTION

A tough, durable high gloss alkyd finish that can be applied directly to steel or used as part of a system. It provides a fast drying, durable finish that will resist mechanical damage.

RECOMMENDED USES



Steel both primed and unprimed. Non-ferrous metals which have been suitably primed and sound previously painted surfaces.

SPECIAL PROPERTIES

Excellent anti-corrosive properties. Provides a tough, high gloss finish that can be handled in 2 hours and is touch dry in around 1 hour.

COLOUR RANGE

Saxe Blue (18E53); Fiesta Red (04E53); Granite (00A09); Dark Green (14C39); Silver (00A01); Saffron Yellow (08E51); Black; White.

FINISH

High gloss.

VOLUME SOLID

50%

COVERAGE



Johnstone's Quick Dry Machinery Enamel will cover at the rate of approximately 10–12 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 1 hour. Hard dry after 4–6 hours. Recoatable after 16 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

TC1 Thinner and Cleaner.

VOC CONTENT

HIGH VOC CONTENT 25–50%. VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

FILM THICKNESS

Wet: 100µm, dry: 42µm.

SIZE

5 Litre.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking materials. If applied directly to steel, the surface must be corrosion free and abraded to provide a key. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354100.

APPLICATION



Stir thoroughly before use. Easy to apply by brush. If more than one can of a colour is to be used in the same area, intermix before use.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with TC1 Thinner and Cleaner. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- PAINT PRODUCT.
- Contains Xylene.
- Contains Ethyl Methyl Ketoxime. May produce an allergic reaction.
- HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.
- Harmful to aquatic organisms. May cause long term adverse effects in the aquatic environment.
- FLAMMABLE.
- Keep away from sources of ignition – No smoking.
- Use only in well ventilated areas.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – **DO NOT USE SOLVENT OR THINNERS.**
- In case of insufficient ventilation wear suitable respiratory protective equipment.
- Wear suitable protective clothing and gloves.
- If swallowed, seek medical advice immediately and show this container or label.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

