

# 4.1

# Anti-Condensation Paint

## DESCRIPTION

A white, water-borne paint which provides a thick matt coating for interior surfaces. Reduces condensation by insulating the substrate and absorbing an amount of the condensed water and releasing it back into the atmosphere over time. Prevents unsightly staining due to condensation runs.

## RECOMMENDED USES



Can be used on most interior surfaces, after suitable preparation and priming, where intermittent water condensation is a problem.

## SPECIAL PROPERTIES

Reduces condensation by absorbing the condensed water and allowing it to be slowly released back into the atmosphere.

## COLOUR RANGE

Brilliant White.

## FINISH

Matt.

## VOLUME SOLID

24%.

## COVERAGE



Johnstone's Anti-Condensation Paint will cover at the rate of approximately 13 square metres per litre depending on the nature and porosity of the surface being painted.

## DRYING TIME



Touch dry in 1 hours.  
Recoat after 2 hours.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

## THINNER

Water.

## VOC CONTENT

LOW VOC CONTENT 0.30–7.99%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 75g/l (2007) / 30g/l (2010).  
This product contains max 15g/l VOC.

## FILM THICKNESS

Wet: 200µm, dry: 70µm.

## SIZE

5 Litre

## PREPARATION

All surfaces to be painted should be sound, clean, dry and free from grease. Remove all loose and defective paint. Lightly abrade glossy areas with abrasive paper. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding. Treat any mould or lichen with Johnstone's Sterilisation Wash before removing with a scraper or stiff brush, then treat surface again with Johnstone's Sterilisation Wash. Prime all areas of damp plaster or brickwork with Johnstone's Damp Proof Paint. Prime bare metal areas with Johnstone's Universal Primer. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354100.

## APPLICATION



Stir well before use. Suitable for application by brush or conventional spray. Apply two full coats. Do not apply when air or surface temperature is below 10°C. Brush marks can be camouflaged by stippling. The application of a protective coat of Johnstone's Anti-Mould Acrylic over the dry film of Johnstone's Anti-Condensation Paint is recommended.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- PAINT PRODUCT.
- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.

## PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.



SigmaKalon DECORATIVE COATINGS UK AND IRELAND, SIGMAKALON UK LIMITED

Huddersfield Road, Birstall, Batley, West Yorkshire WF17 9XA Telephone: 01924 354000 Facsimile: 01924 354001 www.johnstones-paints.co.uk