

**PRODUCT DESCRIPTION & USE**

Armstead Trade Floor Paint is a professional quality, solvent-based general purpose floor paint. Suitable for use on interior, concrete, wood and metal surfaces. Resistant to foot traffic and light rubber wheeled vehicular traffic.

**KEY BENEFITS**

- **Tough & durable smooth floor finish**
- **Resistant to foot traffic**
- **For light industrial use**

**PACK SIZE**

5L

**COLOUR RANGE**

Visit [armsteadtrade.co.uk](http://armsteadtrade.co.uk) for full colour range including:

BS4800:	98 colours
RAL:	45 colours
NCS 1 & 2:	2 colours

**FILM PROPERTIES**

**Chemical Resistance:** Resistant to mild chemical fume attack where there is likely to be spillage of solvents, chemicals, products, foodstuffs etc. specialist coatings.

**Heat Resistance:** Generally resistant to heat up to 90°C

**Water Resistance:** Resistant to repeated and regular washing with water and detergents but not suitable for use on floors that are likely to be continuously wet.

**COMPOSITION (NOMINAL)**

**Pigment:** Lightfast Pigments.

**Binder:** Alkyd

**Solvent:** White Spirit.

**VOLUME SOLIDS**

35% (nominal) for Brilliant White, colours will vary.

**SURFACE PREPARATION**

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and salts. New plaster and masonry must be fully dry before priming. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

**APPLICATION**

Brush or roller.

For Health and safety reasons related to all solvent-based paints, spray application is not recommended. As with other solvent-based paints, do not apply in temperatures below 5°C (as recommended by British Standard BS 6150).

**SYSTEM INFORMATION**

Stir thoroughly before use.

The normal recommendation is to apply 1 or 2 coats of **Armstead Trade** Floor Paint.

**PRACTICAL COVERAGE**

On smooth surfaces of average porosity, a litre of paint is sufficient to apply one coat to an area of up to 16m<sup>2</sup>

**THINNING**

For sealing new or bare surfaces add up to 1 part of white spirit to 10 parts of paint. For normal use thinning is not usually necessary.

**FILM THICKNESS**

*Film thickness will be dependent on the coverage achieved.*

**Wet:** 52-73 microns.

**Dry:** 25-35 microns.

**VOLUME SOLIDS**

48% (nominal).

**SURFACE PREPARATION**

Surfaces must be clean, dry (less than 5.5 on protimeter screed scale) and free from all defective or poorly adhering material. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. New or bare porous surfaces should be sealed with a coat. Armstead Trade Floor paint thinned with up to 1 part white spirit to 10 parts of paint.

**Note:** Do not use in areas of heavy industrial use, aggressive environments, car showrooms or garage floors that are in prolonged contact or where silicate hardeners have been used, Terrazzo and Granolithic or substrates that have not fully dried out. This material is intended for light industrial/ domestic situations. Some concrete floors may take up 12 months to dry in depth. Do not use in areas of constant high humidity such as shower rooms and swimming pools etc.

**Note:** Special precautions should be taken during surface preparation of pre-1990s paint surfaces over wood and metal as may contain harmful lead.

**DRYING TIMES**

**Touch Dry:** 4-6 hours\*

**Recoat:** 16-24 hours\*

\*Dependent upon temperature and humidity

**Note:** It is essential to allow the coated floor to dry for a minimum of 24 hours under well-ventilated conditions before use.

**RESPONSIBLE CLEANING**

**Cleaning After Final Use:** Cleaning your brushes and rollers immediately after their final use ensures they can be reused for multiple projects, saving you money and reducing waste.

**Cleaning:**

1. **Remove Excess Paint:** Scrape off excess paint into container for future projects.
2. **Use Paint Thinner:** Use a paint thinner to clean brushes and rollers.
3. **Reuse Paint Thinner:** Allow the paint solids to settle and reuse the thinner by pouring the clear liquid into another container.
4. **Responsible Disposal:** Dispose of the remaining solids and used thinner at a hazardous waste facility. Do not pour any solvent-based paint, paint thinner or wash water down the drain or onto the ground.

***Do not flush paint down the drain, including when cleaning painting tools***



# FLOOR PAINT

AM305  
Issued 10/2025

## TRANSPORTATION & STORAGE

Do not use or store in extremes of temperature and protect from  
they to prevent spillage, please store and transport upright.

## VOC

EU limit value for this product (cat. : A/a) : 500g/l (2010)

This product contains max. 450g/l VOC

VOC Content High 25% – 50% VOCs (Volatile Organic Compounds)  
contribute to atmospheric pollution.

## FURTHER SUPPORT

Online: [www.armsteadtrade.co.uk](http://www.armsteadtrade.co.uk)

Email: [armstead.advice@akzonobel.com](mailto:armstead.advice@akzonobel.com)

Phone: 0333-222-70-70

Safety datasheets are available to download on  
[armsteadtrade.co.uk](http://armsteadtrade.co.uk)

AkzoNobel, the AkzoNobel logo and Armstead are trademarks of  
the AkzoNobel group © AkzoNobel 2023