

PRODUCT DESCRIPTION & USE

Armstead Trade Quick Dry Wood Primer Undercoat is a professional quality, fast drying, water-based wood primer with good opacity and excellent adhesion that does the work of both a primer and an undercoat. Suitable for both interior and exterior use.

KEY BENEFITS

- Quick drying
- Excellent adhesion
- For interior and exterior use

PACK SIZES

COLOUR RANGE

White only.

COMPOSITION (NOMINAL)

Pigment: Lightfast Pigments.
 Binder: Acrylic Copolymer.
 Solvent: Water.

VOLUME SOLIDS

35% (nominal).

SURFACE PREPARATION

Surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. Thoroughly rub down previously painted surfaces, using 'wet flattening' methods where possible, then wipe off with a damp, lint free cloth. Treat any knots in wood with a suitable knotting solution. Any surface defects must be filled with a suitable filler.

Note: Special precautions should be taken during surface preparation of pre-1990s paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION


Brush, roller, & airless spray.

As with other water-based paints, do not apply in temperatures below 8°C (as recommended by British Stand

SYSTEM INFORMATION

Stir thoroughly before use.

New or bare surfaces:

2 coats of **Armstead Trade** Quick Dry Wood Primer Undercoat.

Previously painted surfaces:

1 coat of **Armstead Trade** Quick Dry Wood Primer Undercoat.

Allow you to dry for a minimum of 2 hours between coats, then, apply an appropriate **Armstead Trade** paint system.

PRACTICAL COVERAGE


Up to 12m² per litre on smooth surfaces of average porosity.

THINNING
Sealing new/bare surfaces:

Add up to 1 part clean water to 5 parts paint.

Normal use:

Add up to 1 part clean water to 10 parts paint.

Airless spray application:

Add up to 1 part clean water to 5 parts paint.

SPRAY RECOMMENDATIONS

Airless Spray: A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm² (2000 lb/sq in) with a spray tip size 0.43mm (17 thou) and a spray tip angle 60°.

DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)


Touch Dry: 1 hour*
 Recoat: 2 hours*

*Dependent upon temperature & humidity

CLEANING UP


After use, remove as much paint as possible from brushes before cleaning with clean water.

TRANSPORTATION & STORAGE

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat A/d) : 150g/l (2007) / 130g/l (2010) This product contains max. 30g/l VOC

VOC Content - Trace <0.1%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.



QUICK DRY WOOD PRIMER UNDERCOAT

AM101

AkzoNobel

Issued August 2023

FURTHER SUPPORT

Online: www.armsteadtrade.co.uk

Email: armstead.advice@akzonobel.com

Phone: 0333-222-70-70 Please visit



Like us on Facebook



Videos on YouTube



Follow us on Twitter



Available on the
App Store

www.armsteadtrade.co.uk to download safety sheet

Let's create together a better future for our planet.

Find out how at: www.armsteadtrade.co.uk/sustainability

AkzoNobel, the AkzoNobel logo, Armstead and Planet Possible are

trademarks of the AkzoNobel group © AkzoNobel 2023