



## SAFETY DATA SHEET

ANTI-SLIP DECKING OIL (TOPCOAT)

Page: 1

Compilation date: 22/02/2017

Revision date: 13/06/2018

Revision No: 3

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** ANTI-SLIP DECKING OIL (TOPCOAT)

**Product code:** DOASGEN

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC15: Non-metal-surface treatment products.

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** J.V. Barrett & Co Ltd

St Ivel way

Warmley

Bristol

BS30 8TY

United Kingdom

**Tel:** 01179600060

**Fax:** 01179352437

**Email:** [sales@barrettine.co.uk](mailto:sales@barrettine.co.uk)

#### 1.4. Emergency telephone number

**Emergency tel:** +44 (0) 1179 600060 (Office hours only 8am - 5pm Mon- Thurs. 8 am - 4.30 pm  
Fri.) +44 (0) 1270 502891 (Out of hours emergency number)

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CLP:** Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066; -: EUH208

**Most important adverse effects:** Repeated exposure may cause skin dryness or cracking. Contains 3-iodo-2-propynyl butylcarbamate, 1-acetyl-4-(3-dodecyl-2,5-dioxo-1-pyrrolidiny)-2,2,6,6-tetramethylpiperidine. May produce an allergic reaction. Flammable liquid and vapour. May cause drowsiness or dizziness.

#### 2.2. Label elements

**Label elements:**

**Hazard statements:** EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains 3-iodo-2-propynyl butylcarbamate, 1-acetyl-4-(3-dodecyl-2,5-

[cont...]

# SAFETY DATA SHEET

## ANTI-SLIP DECKING OIL (TOPCOAT)

Page: 2

dioxo-1-pyrrolidinyl)-2,2,6,6-tetramethylpiperidine. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark



**Signal words:** Warning

**Precautionary statements:** P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261: Avoid breathing fumes/vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/eye protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water and soap.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call POISON CENTER/doctor if you feel unwell.

P403+P235: Store in a well-ventilated place. Keep cool.

P233: Keep container tightly closed.

P405: Store locked up.

P501: Dispose of contents/container to hazardous or special waste collection point.

### 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

**\* Hazardous ingredients:**

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS - REACH registered number(s): 01-2119463258-33-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
--------	-----	-----------	--------------------	---------

[cont...]

# SAFETY DATA SHEET

## ANTI-SLIP DECKING OIL (TOPCOAT)

Page: 3

919-857-5	-	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	30-50%
-----------	---	---	-------------------------------------------------------------------	--------

PARAFFIN WAX - REACH registered number(s): 01-2119488075-30-XXXX

232-315-6	8002-74-2	Substance with a Community workplace exposure limit.	-	1-10%
-----------	-----------	------------------------------------------------------	---	-------

3-IODO-2-PROPYNYL BUTYLCARBAMATE - REACH registered number(s): 01-2120762115-60-XXXX

259-627-5	55406-53-6	-	Acute Tox. 3: H331; Acute Tox. 4: H302; STOT RE 1: H372; Eye Dam. 1: H318; Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	0.1-1%
-----------	------------	---	-----------------------------------------------------------------------------------------------------------------------------------------------	--------

2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT - REACH registered number(s): 01-2119979088-21-XXXX

245-018-1	22464-99-9	-	Repr. 2: H361	0.1-1%
-----------	------------	---	---------------	--------

1-ACETYL-4-(3-DODECYL-2,5-DIOXO-1-PYRROLIDINYL)-2,2,6,6-TETRAMETHYLPYPERIDINE - REACH registered number(s): 01-0000015927-59-XXXX

411-930-5	106917-31-1	-	Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	<0.1%
-----------	-------------	---	-----------------------------------------------------------------------------------------	-------

### Section 4: First aid measures

#### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

### Section 5: Fire-fighting measures

[cont...]

# SAFETY DATA SHEET

## ANTI-SLIP DECKING OIL (TOPCOAT)

Page: 4

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers. Do not use water jet

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS. Refer to section 13 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Avoid incompatible materials and conditions - see section 10 of SDS.

[cont...]

# SAFETY DATA SHEET

## ANTI-SLIP DECKING OIL (TOPCOAT)

Page: 5

### 7.3. Specific end use(s)

Specific end use(s): PC15: Non-metal-surface treatment products.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

Workplace exposure limits: No data available.

### DNEL/PNEC Values

Hazardous ingredients:

#### HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

Type	Exposure	Value	Population	Effect
DNEL	Dermal (repeated dose)	208 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation (repeated dose)	871 mg/m <sup>3</sup> /8H	Workers	Systemic
DNEL	Dermal (effects on fertility)	125 mg/kg bw/day	Consumers	Systemic
DNEL	Inhalation (repeated dose)	185 mg/m <sup>3</sup> /24H	Consumers	Systemic
DNEL	Oral	125 mg/kg bw/day	Consumers	Systemic

#### 3-IODO-2-PROPYNYL BUTYLCARBAMATE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	70 µg/m <sup>3</sup>	Workers	Systemic
DNEL	Inhalation (repeated dose)	23 µg/m <sup>3</sup>	Workers	Systemic
DNEL	Inhalation	1.16 mg/m <sup>3</sup>	Workers	Local
DNEL	Inhalation (repeated dose)	1.16 mg/m <sup>3</sup>	Workers	Local
DNEL	Dermal (repeated dose)	2 mg/kg bw/day	Workers	Systemic
PNEC	Fresh water	500 ng/l	-	-
PNEC	Fresh water sediments	17 µg/kg	-	-
PNEC	Marine water	46 ng/l	-	-
PNEC	Marine sediments	1.6 µg/kg	-	-
PNEC	Microorganisms in sewage treatment	440 µg/l	-	-
PNEC	Soil (agricultural)	5 µg/kg	-	-

#### 2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT

Type	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	32 mg/m <sup>3</sup>	Workers	Systemic
DNEL	Inhalation (repeated dose)	8 mg/m <sup>3</sup>	General Population	Systemic
DNEL	Dermal (repeated dose)	6.49 mg/kg bw/day	Workers	Systemic
DNEL	Dermal (repeated dose)	3.25 mg/kg bw/day	General Population	Systemic
DNEL	Oral (repeated dose)	2.5 mg/kg bw/day	General Population	Systemic
PNEC	Fresh water	360 µg/l	-	-

[cont...]

# SAFETY DATA SHEET

## ANTI-SLIP DECKING OIL (TOPCOAT)

Page: 6

PNEC	Fresh water sediments	6.37 mg/kg	-	-
PNEC	Marine water	36 µg/l	-	-
PNEC	Marine sediments	637 µg/kg	-	-
PNEC	Microorganisms in sewage treatment	71.7 mg/l	-	-
PNEC	Soil (agricultural)	1.06 mg/kg	-	-

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses.

**Skin protection:** Protective clothing.

**Environmental:** The floor of the storage room must be impermeable to prevent the escape of liquids. Ensure all engineering measures mentioned in section 7 of SDS are in place. Storage should be placed inside a fully bunded area of sufficient size to contain the volume plus 10%.

### Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Pale brown

**Odour:** Characteristic odour

**Evaporation rate:** No data available.

**Oxidising:** No data available.

**Solubility in water:** Insoluble

**Viscosity:** No data available.

**Boiling point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**Flash point°C:** 40- 60

**Autoflammability°C:** No data available.

**Relative density:** No data available.

**VOC g/l:** 498

**Melting point/range°C:** No data available.

**upper:** No data available.

**Part.coeff. n-octanol/water:** No data available.

**Vapour pressure:** No data available.

**pH:** No data available.

#### 9.2. Other information

**Other information:** No data available.

### Section 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

[cont...]

# SAFETY DATA SHEET

## ANTI-SLIP DECKING OIL (TOPCOAT)

Page: 7

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

#### HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

GASES	RBT	24H LD50	> 5000	mg/kg
ORAL	RAT	LD50	> 5000	mg/kg
VAPOURS	RAT	8H LC50	> 5000	mg/m3

#### PARAFFIN WAX

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

#### 3-IODO-2-PROPYNYL BUTYLCARBAMATE

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	300 to 500	mg/kg
VAPOURS	RAT	4H LC50	0.67	mg/l

#### 2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT

DERMAL	RAT	LD50	2000	mg/kg
ORAL	RAT	LD50	2043-5000	mg/kg
VAPOURS	RAT	8H LC50	110	mg/m3

[cont...]

# SAFETY DATA SHEET

## ANTI-SLIP DECKING OIL (TOPCOAT)

Page: 8

### 1-ACETYL-4-(3-DODECYL-2,5-DIOXO-1-PYRROLIDINYL)-2,2,6,6-TETRAMETHYLPYPERIDINE

ORAL	RAT	LD50	>3000	mg/kg
VAPOURS	RAT	4H LC50	2.61	mg/l

#### Relevant hazards for product:

Hazard	Route	Basis
STOT-single exposure	-	Hazardous: calculated

#### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.  
Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Other information:** Not applicable.

#### Section 12: Ecological information

##### 12.1. Toxicity

#### Hazardous ingredients:

##### HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

ALGAE	72H EbL50	>1000	mg/l
ALGAE	72H ErL50	>1000	mg/l
Daphnia magna	48H EL50	>1000	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LL50	>1000	mg/l

##### PARAFFIN WAX

ALGAE	NOEL	>100	mg/l
Daphnia magna	EL50	>10000	mg/l
Daphnia magna	NOEL	10	mg/l
FISH	LL50	>100	mg/l

##### 3-IODO-2-PROPYNYL BUTYLCARBAMATE

Daphnia magna	48H EC50	0.16	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	0.67	mg/l
Scenedesmus Subspicatus	72H ErC50	0.053	mg/l

[cont...]



# SAFETY DATA SHEET

## ANTI-SLIP DECKING OIL (TOPCOAT)

Page: 9

### 2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT

ALGAE	96H EC10	32	mg/l
DAPHNIA	48H EC50	62.5	mg/l
FISH	96H LC50	100	mg/l

### 1-ACETYL-4-(3-DODECYL-2,5-DIOXO-1-PYRROLIDINYL)-2,2,6,6-TETRAMETHYLPIPERIDINE

Daphnia magna	48H EC50	0.27	mg/l
FISH	96H LC50	>0.5	mg/l

#### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

#### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

#### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Waste code number:** 03 02 05

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### Section 14: Transport information

#### 14.1. UN number

**UN number:** UN1268

#### 14.2. UN proper shipping name

**Shipping name:** PETROLEUM PRODUCTS, N.O.S.  
(HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS; LOW BOILING POINT NAPHTHA - UNSPECIFIED - NAPHTHA (PETROLEUM), LIGHT STEAM CRACKED)

[cont...]

# SAFETY DATA SHEET

## ANTI-SLIP DECKING OIL (TOPCOAT)

Page: 10

### 14.3. Transport hazard class(es)

Transport class: 3

### 14.4. Packing group

Packing group: III

### 14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

### 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** \* according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

This safety data sheet is prepared in accordance with Commission Regulation (EC) No 1272/2008.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.  
EUH208: Contains 3-iodo-2-propynyl butylcarbamate, 1-acetyl-4-(3-dodecyl-2,5-dioxo-1-pyrrolidinyl)-2,2,6,6-tetramethylpiperidine. May produce an allergic reaction.  
H226: Flammable liquid and vapour.  
H302: Harmful if swallowed.  
H304: May be fatal if swallowed and enters airways.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H318: Causes serious eye damage.  
H331: Toxic if inhaled.  
H336: May cause drowsiness or dizziness.  
H361: Suspected of damaging fertility or the unborn child.

[cont...]

# SAFETY DATA SHEET

## ANTI-SLIP DECKING OIL (TOPCOAT)

Page: 11

H372: Causes damage to organs through prolonged or repeated exposure.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.