TEREBINE DRIERS

A specially blended solution of liquid metallic driers to speed up the drying time of most solvent / oil based conventional air-drying paints during cold weather or adverse conditions.



250ml_e

Barrettine

SHAKE WELL

Instructions for use: Add a maximum of 10 ml per 1 litre of paint and mix thoroughly (cap holds 10-11mls). Suitable for use with Gloss Oil Paints, Polyurethanes, Varnishes and most conventional air-drving paints. Caution: Not suitable for water based or cellulose paints. It is recommended to conduct a test to ensure compatibility with other paint resin systems and that the dry paint film finish is acceptable. Recommended for use only when the ambient temperature is between 2 - 10 Celsius.

HEALTH & SAFETY

Contains: Cobalt(II) 2-ethylhexanoate, Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (contains less than 0.01 % w/w benzene) HA7ARD STATEMENTS

• Flammable liquid and vapour • May be fatal if swallowed and enters airways • May cause an allergic skin reaction • May cause drowsiness or dizziness • Harmful to aquatic life with long lasting effects • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking • Keep container tightly closed • Avoid breathing fume, vapours, mist, spray • Use only outdoors or in a well-ventilated area • Dispose of contents/

container in accordance with local/national/international regulations • Repeated exposure may cause skin drvness or crackina.

UN No. 1263



St. Ivel Way, Warmley, Bristol BS30 8TY T+44 (0) 117 960 0060 F+44 (0) 117 935 2437 E sales@barrettine.co.uk www.barrettine.co.uk