

DESCRIPTION

Johnstone's StainAway is an innovative, high opacity wall and ceiling paint. It contains Stain Blocking Technology, permanently isolating even the most persistent stains such as smoke damage, nicotine damage and water stains. Johnstone's StainAway is a stain sealer and finish in one product. It has a dead flat finish that hides surface imperfections, whilst providing a high level of durability achieving class 1 scrub rating ISO 11998.

RECOMMENDED USES



Stain isolator and finish for all types of interior walls and ceilings both bare and previously painted including plaster, plasterboard, concrete, ceiling tiles and wallcoverings .

TYPE OF SUBSTRATE

Gives the same stain blocking performance when applied to a variety of suitably prepared and primed surfaces such as metal, wood, melamine, glazed tiles etc.

COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

FINISH

Dead Matt Finish.

VOLUME SOLID

43%

COVERAGE



Up to 9m² per litre depending on the nature and porosity of the surface.

DRYING TIME



Touch Dry 1 hour
Recoat after 4 hours.

TRANSPORTATION & STORAGE

No more than 8kg (5Ltr) 16kg (10ltr).

THINNER

Clean water.

VOC CONTENT

MINIMAL VOC CONTENT 0 - 0.29%

VOC (Volatile Organic Compounds) contribute to atmospheric pollution

EU limit value for this product (Cat A/a): 30g/l (2010)

FILM THICKNESS

Wet 110 microns and Dry 48 microns.

CLEANING STAINS

Apply all-purpose cleaner to sponge or soft cloth and wipe away stain from surface and allow to dry.

KEY PROPERTIES

- Innovative stain Isolating Properties
- High Opacity
- Dead Flat Finish
- Excellent Durability

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Where water damage has occurred, ensure the leak is fixed and the area is dry before painting. If severe remove heavy nicotine, soot and smoke deposits as much as possible, in keeping with basic painting practices. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For additional information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Ensure good ventilation during application and drying. Stir well. Easy to apply by brush and roller. Also suitable for application by spray. Avoid over spreading. Some strong or contrasting stains may require a further coats. Seal absorbent surfaces such as new plaster, plaster boards filler etc. with a coat of StainAway thinned up to 10% with clean water. For alternative surfaces such as wood, metal melamine, tiles etc. use the appropriate Johnstone's Primer. Ensure good ventilation during application and drying. Do not apply in temperatures below 8°C or in damp conditions. **Spray Application:** AIRLESS SPRAY: Un-thinned: Spray @ 2000 PSI / 207 bar with 517 tip.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Do not breathe spray. Wear respiratory protection.
- Do not get in eyes, on skin or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Safety data sheet available on request

SIZES

2.5 Litre, 5 Litre and 10 Litre.