

MANOR

PRODUCT DATA SHEET



ANTI SLIP ADDITIVE

INTENDED USE

DECORATION OF BUILDINGS

Anti Slip Additive is used in environments where a smooth glossy floor coating is considered to be potentially slippery under typical conditions of use.

Anti Slip Additive is effective on dry, clean floors, but if floors are damp, wet or greasy it makes little difference

For use with Linotex Floor Enamel, 2 Pack Epoxy Finish and Promastic 600CT floor coatings, mainly for industrial applications

SUITABLE SUBSTRATES AND PREPARATION

Industrial Concrete Floors

AVAILABILITY

4.5kg (approx) in 2.5 litre container

PRODUCT INFORMATION (TYPICAL FIGURES)

Composition	Aggregate
Volume Solids	n/a
Weight Solids	n/a
VOC content	n/a
Supply Viscosity	n/a
Typical film thickness	n/a
Theoretical coverage	Can be mixed with paint at any ratio from 2:1 to 5:1 (vol:vol)
Dry heat resistance	n/a
Flash Point	n/a

APPLICATION DETAILS

Anti Slip Additive is a transparent fine sand which can be either sprinkled on the coating immediately after application and before it has dried out, or, mixed with the paint.

Airless spray: **cold** n/a
 heated n/a
Conventional spray n/a
Brush Roller n/a
Thinner n/a

Film thickness per coat

	<u>Dry</u>	<u>Wet</u>
Minimum	n/a	n/a
Maximum	n/a	n/a

DRYING AND RECOATING

n/a

<u>Substrate temperature</u>	<u>Touch Dry</u>	<u>Overcoating times</u>	
		Minimum	Maximum
10C	n/a	n/a	n/a
20C	n/a	n/a	n/a

Note Over a period of time the aggregate will become worn and may require regular recoating to maintain the original anti slip properties.

Environmental conditions n/a
Overcoating / repainting n/a

SHELF LIFE

Store in cool, dry conditions, typically 5-25C. After a period of storage the product should be thoroughly stirred. Usable life is 2 years from date of manufacture in unopened containers.

SAFETY PRECAUTIONS

Refer to Manor Safety Data Sheet

LIMITATIONS

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied however, since the conditions of use are beyond our control. This data sheet does not constitute a specification.

A Painting Guide can be accessed via our website which provides additional information on paint and painting and definitions of terminology.

In case of doubt as to the suitability of the product please consult our Technical Department. If you are advised that the paint can be used in a manner not specified on this datasheet our Technical Department will confirm this to you in writing. Do not use paint prior to receiving this confirmation.

References to other primers, topcoats, cleaners and thinners are to the Manor Product of that name only.

This data sheet supercedes all previous issues.

REFERENCES

Amended date: November 21, 2012

Reference and number:ADNSLIP- 4