



# STABILISING PRIMER

AM 301  
Issued 10/2025

## PRODUCT DESCRIPTION & USE

Armstead Trade Stabilising Primer is a professional quality, clear, solvent-based primer. It is formulated to seal powdery exterior masonry surfaces that can be used with most decorative finishes.

## KEY BENEFITS

- Seals porous, dry & powdery surfaces
- Resists alkali attack
- Use with Armstead Trade Masonry finishes.

## PACK SIZES

5L

## COLOUR RANGE

Clear

## COMPOSITION (NOMINAL)

Pigment:	N/A.
Binder:	Acrylic Copolymer
Solvent:	White Spirit.

## VOLUME SOLIDS

9% (nominal).

## SURFACE PREPARATION

All surfaces should be thoroughly prepared by vigorous scraping and brushing to remove any loose or flaking paint and dirt. A stiff fibre brush will give better results than a wire brush, as any wire that becomes embedded in the wall will rust and stain the new paint. Treat any existing mould or organic growth with \*Weathershield Multi-Surface Fungicidal Wash. Make good minor defects. Use a sand and cement mix for larger holes and cracks.

Note: Do not seal sound new or bare surfaces with stabilising primer.

Special precautions should be taken during surface preparation of pre-1990s paint surfaces over wood and metal as they may contain harmful lead.

## APPLICATION

Brush or roller. For Health and Safety reasons related to all solvent-based paints, spray application is not recommended.

As with other solvent-based paints, do not apply in temperatures below 5°C (as recommended by British Standard BS 6150).

## SYSTEM INFORMATION

Stir or Shake container vigorously before use.

After suitable preparation, the normal recommendation is to apply one coat of Armstead Trade Stabilising Primer to powdery surfaces, followed by the appropriate Armstead Trade exterior finishing system.

## PRACTICAL COVERAGE

A guide to the practical coverage which can be achieved under normal conditions is 10m<sup>2</sup>/litre

## DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)

Touch Dry: 2-4 hours\*

Recoat: 16-24 hours\*

\*Dependent upon temperature & humidity

## RESPONSIBLE CLEANING

**Cleaning After Final Use:** Cleaning your brushes and rollers immediately after their final use ensures they can be reused for multiple projects, saving you money and reducing waste.

### Cleaning:

1. **Remove Excess Paint:** Scrape off excess paint into container for future projects.
2. **Use Paint Thinner:** Use a paint thinner to clean brushes and rollers.
3. **Reuse Paint Thinner:** Allow the paint solids to settle and reuse the thinner by pouring the clear liquid into another container.
4. **Responsible Disposal:** Dispose of the remaining solids and used thinner at a hazardous waste facility. Do not pour any solvent-based paint, paint thinner or wash water down the drain or onto the ground.

***Do not flush paint down the drain, including when cleaning painting tools***

## TRANSPORTATION & STORAGE

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

## VOC

EU limit value for this product (cat A/h) : 750g/l (2007) / 750g/l (2010) This product contains max. 749g/l VOC

VOC Content Very High more than 50%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

## FURTHER SUPPORT

Online: [www.armsteadtrade.co.uk](http://www.armsteadtrade.co.uk)

Email: [armstead.advice@akzonobel.com](mailto:armstead.advice@akzonobel.com)

Phone: 0333-222-70-70

Please visit [www.armsteadtrade.co.uk](http://www.armsteadtrade.co.uk) to download safety sheet

Safety datasheets are available to download on [armsteadtrade.co.uk](http://armsteadtrade.co.uk)

AkzoNobel, the AkzoNobel logo and Armstead are trademarks of the AkzoNobel group © AkzoNobel 2023