

# **BLACKFRIAR PAINTS LTD**

## **TECHNICAL DATA SHEET**

### **BF032 Blackfriar Aluminium Paint.**

Revision  
date:  
12/11/13

<b><u>Product Information</u></b>	<b><u>Technical Spec</u></b>	<b><u>Recommended Spreading Rate</u></b>
<p><b><u>Description</u></b></p> <p>A bright metallic paint for metal and wood.</p>	<p><b><u>Composition</u></b></p> <p>Based on a blend of Hydrocarbon Resin with Linseed Oil Varnish Media</p>	<p>Up to 14m<sup>2</sup>/L</p>
<p><b><u>Usage/purpose</u></b></p> <p>Ideal for pipework, caravans, cycles, gates, car wheels etc. Interior or Exterior</p>	<p><b><u>Properties</u></b></p> <p>VOC Content: EU limit Value (Cat A/i): 500g/L This product contains max 500g/L</p>	<p><b><u>Thinning</u></b></p> <p>Not recommended</p>
<p><b><u>Characteristics</u></b></p> <p>A smooth finish that is highly reflective and protective.</p>	<p><b><u>Performance</u></b></p> <p>Tough and durable.(see limitations) Heat resistant to 150°C.</p>	<p><b><u>Drying Time</u></b></p> <p>Touch dry in 2-4 hours Recoat after 16 hours under normal conditions (20°C 50% r/h).</p>
<p><b><u>Finish</u></b></p> <p>High Gloss</p>	<p><b><u>Surface Preparation</u></b></p> <p>Ensure the substrate to be painted is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease etc). Remove all signs of rust to a clean bright surface. Where necessary prime new and bare areas with appropriate Blackfriar Primer</p>	<p><b><u>Cleaning</u></b></p> <p>Clean application equipment or spills with white spirit</p>
<p><b><u>Colour(s)</u></b></p> <p>Aluminium silver</p>		<p><b><u>Limitations</u></b></p> <p>On surfaces likely to be handled over-coat with a thin coat of Blackfriar P99 (interior) or Blackfriar Exterior Varnish UV66 (exterior). These will give a slight yellow appearance</p>
<p><b><u>Packaging</u></b></p> <p>250ml, 500ml, 1litre, Larger sizes may be available on request dependant on volume required</p>	<p><b><u>Application Method</u></b></p> <p>Brush, Roller, Spray Ensure products are thoroughly stirred with a broad stirrer. No undercoat is necessary. Apply at least two full coats for protection</p>	<p><b><u>Environmental Info.</u></b></p> <p>Dangerous for the environment</p>
<p><b><u>Disclaimer;</u></b> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.</p>	<p><b>For Technical Enquiries, Material Safety Data sheets Telephone 0191 4113146</b></p>	<p><b>Paint Product</b> UN No. 1263.</p>
		<p><b>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</b></p>