

BLACKFRIAR

BF6451002 ANTI-SLIP DECK COATING
A CLEAR LOW SHEEN DECK COATING. PROVIDES A SLIP RESISTANT FINISH IN WET CONDITIONS
CLEAR PROTECTIVE ANTI-SLIP SURFACE CONTAINS MICRO AGGREGATES EXTERNAL FOR WOOD DECKING AND WALKWAYS
BLACKFRIAR ANTI-SLIP DECK COATING Blackfriar Anti-Slip Deck Coating provides all types of exterior timber decking and walkways with a protective, slip resistant surface. Containing micro-aggregates, this coating gives increased grip in wet conditions while allowing the beauty of wood to show through.
PREPARATION Ensure surface to be treated is clean, thoroughly dry, sound and free from wax, oil or any other contamination. It is important that the substrate is thoroughly dry before application and during the drying period otherwise blanching (whitening) may occur. Existing coatings should be lightly sanded to aid adhesion. Weathered timber should be made good. On bare wood the use of a decking stain is recommended prior to application of this product as this will give the wood better UV resistance and prolong the lifetime of the coating. Ensure new or bare timber is adequately preserved prior to applying wood finishes, apply Blackfriar Goldstar Clear Wood Preservative to untreated timbers where required.
APPLICATION Stir thoroughly prior to use. For best results apply two coats by short pile roller. Allow the first coat to fully dry before applying a second coat. A brush may be used for small or awkward areas. Thinning not recommended.
APPEARANCE Clear, textured, low sheen.
COVERAGE RATE Up to 9m ² /litre per coat.
DRYING TIME Touch dry in 4 - 6 hours. Recoat after 12 hours and within 3 days. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.
PACK SIZES 2.5L
CLEAN UP Remove as much product as possible from application equipment before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.
VOC EU limit value for this product (cat A/i): 500 g/l. This product contains max 500 g/l VOC
LIMITATIONS Do not apply in wet or frosty conditions. The anti-slip properties make this product difficult to clean. This product is not suitable for heavy duty use or steel wheeled vehicles. Do not allow the build up of moss / mould growth or wet leaves etc. as this will impair or even cancel the anti-slip properties.
DISCLAIMER The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.
Tor Coatings Ltd, Portobello Industrial Estate, Birtley, Chester-le-Street, County Durham, DH3 2RE. For Technical Enquiries or Material Safety Data Sheets. Contact sales on 0191 410 6611.