

BLACKFRIAR PAINTS LTD

TECHNICAL DATA SHEET

BF031 Blackfriar Slip Resistant Step Paint

Revision date: 08/01/2007

<p><u>Product Information</u></p> <p><u>Description</u></p> <p>A multi - purpose floor paint with added aggregate to help prevent slipping.</p> <p><u>Usage/purpose</u></p> <p>For interior or exterior use on concrete, wood, and metal. (NB. See limitations)</p> <p><u>Characteristics</u></p> <p>A 'textured' liquid paint with an odour of white spirit.</p> <p><u>Finish</u></p> <p>'Textured' finish</p> <p><u>Colour(s)</u></p> <p>Tile Red</p> <p><u>Packaging</u></p> <p>250ml, 500ml. Larger sizes may be available on request dependant on volume required</p> <p><u>Disclaimer:</u> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p><u>Technical Spec</u></p> <p><u>Composition</u></p> <p>Based on a blend of pigments and aggregates in a long oil alkyd resin blended with a modified rosin phenolic resin.</p> <p><u>Properties</u></p> <p>VOC Content: 378 g/litre.</p> <p><u>Performance</u></p> <p>Tough and durable. Heat resistant to 150°C. Resistant to oil and grease. Prevents concrete dusting.</p> <p><u>Surface Preparation</u></p> <p>Ensure the substrate to be painted is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease etc). On ferrous metal floors remove all signs of rust to a clean bright surface and prime immediately. Prime new/ bare areas with the appropriate Blackfriar primer.</p> <p><u>Application Method</u></p> <p>Brush, Roller, Spray Ensure products are thoroughly stirred with a broad stirrer prior to use. No undercoat required. Apply at least two full coats.</p> <p><u>Recommended Spreading Rate</u></p> <p>13m²/ltr</p> <p>For Technical Enquiries, Material Safety Data Sheets Telephone Sales on 0191 4106611</p>	<p><u>Thinning</u></p> <p>Up to 10% with white spirit</p> <p><u>Drying Time</u></p> <p>Touch dry in 4-6 hours Recoat after 16 hours under normal conditions (20°C 50% r/h). Leave 48 hours before subjecting to heavy traffic.</p> <p><u>Cleaning</u></p> <p>Clean application equipment or spills with white spirit or Blackfriar Brush Cleaner</p> <p><u>Limitations</u></p> <p>New concrete must be left for 6 months to dry before painting. Not suitable for use over power-floated or Granolithic concrete. Do not apply to surfaces suffering from rising damp. Situations can arise where the steps may be slippery, such as a build up of moss, accumulation of wet leaves, during a heavy downpour and spillages of any liquids. Caution should be exercised when walking on any steps in these situations.</p> <p><u>Environmental Info.</u> Dangerous for the environment</p> <p>Paint Product UN No. 1263.</p> <p>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</p>
--	---	---