

BLACKFRIAR PAINTS LTD
TECHNICAL DATA SHEET
BF084 Blackfriar Boiled Linseed Oil

Revision date: 12/11/13

<u>Product Information</u>	<u>Technical Specification</u>	<u>Recommended Spreading Rate</u>
<p><u>Description</u></p> <p>A boiled Linseed Oil</p>	<p>Boiled linseed oil.</p>	<p>Dependant on the absorbency of the wood.</p>
<p><u>Usage/purpose</u></p> <p>Suitable for use on bare woods other than oak. Also used for softening metal glazing putty.</p>	<p><u>Properties</u></p> <p>VOC Content: EU Limit Value (catA/e): 400g/L This product contains max 100g/L</p>	<p><u>Thinning</u></p> <p>Up to 10% with white spirit or Blackfriar Genuine Turpentine.</p>
<p><u>Characteristics</u></p> <p>Boiled Linseed Oil dries to an attractive 'ruby' tint with a slightly glossy film.</p>	<p><u>Performance</u></p> <p>Interior or exterior finish. NB. If used externally, will require regular maintenance.</p>	<p><u>Drying Time</u></p> <p>12 hours under normal conditions (20°C 50% r/h).</p>
<p><u>Finish</u></p> <p>Slight gloss</p>	<p><u>Surface Preparation</u></p> <p>Ensure the substrate to be oiled is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease, polish etc). When applying to new wood thin the first coat with up to 10% white spirit or Blackfriar Genuine Turpentine.</p>	<p><u>Cleaning</u></p> <p>Clean application equipment or spills with white spirit or Blackfriar Brush cleaner</p>
<p><u>Colour(s)</u></p> <p>Clear with a ruby hue</p>	<p><u>Application Method</u></p> <p>Ensure the Boiled Linseed Oil is <u>thoroughly shaken</u>. Apply sparingly with a lint free rag. Ensure the oil is worked in to the wood and remove any excess from the wood when finished.</p>	<p><u>Limitations</u></p> <p>When used outside finish must be maintained regularly (<u>at least</u> once a year). Do <u>not</u> use on Oak. Rags used with this material are combustible. Destroy all rags after use by burning outside or lay cloths in single layers to dry before disposal.</p>
<p><u>Packaging</u></p> <p>250ml, 2.5 litre. Larger sizes may be available on request, dependent on volumes.</p>		<p><u>Environmental Info.</u></p> <p>Dangerous for the environment</p>
<p><u>Disclaimer;</u></p> <p>The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.</p>	<p>For Technical Enquiries or Material Safety Data Sheets, Contact Sales on 0191 4113146</p>	<p>Paint Product UN No. 1263.</p>
		<p>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</p>