

# **BLACKFRIAR PAINTS LTD**

## **TECHNICAL DATA SHEET**

### **BF016 Blackfriar Brick and Tile Paint.**

Revision  
date:  
12/11/13

<p><b><u>Product Information</u></b></p> <p><b><u>Description</u></b></p> <p>A matt red paint for brickwork and tiles.</p> <p><b><u>Usage/purpose</u></b></p> <p>To add/restore colour to faded brickwork and tiles</p> <p><b><u>Characteristics</u></b></p> <p>A weather resistant matt finish that is self-cleaning and protective.</p> <p><b><u>Finish</u></b></p> <p>Matt</p> <p><b><u>Colour(s)</u></b></p> <p>Russet Red</p> <p><b><u>Packaging</u></b></p> <p>250ml, 500ml, 1litre, 2.5litre. Larger sizes may be available on request dependant on volume required</p> <p><b><u>Disclaimer;</u></b> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.</p>	<p><b><u>Technical Spec</u></b></p> <p><b><u>Composition</u></b></p> <p>Based on a blend of earth pigments and a durable long oil alkyd resin.</p> <p><b><u>Properties</u></b></p> <p>VOC Content: EU limit (catA/i): 500g/L This product contains max 500g/L</p> <p><b><u>Performance</u></b></p> <p>Ideal for use inside or outside. Provides an attractive finish to fading brickwork, roof tiles etc.</p> <p><b><u>Surface Preparation</u></b></p> <p>Ensure the substrate to be painted is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease etc). On sound surfaces a primer is not required.</p> <p><b><u>Application Method</u></b></p> <p>Brush, Roller, Spray Ensure products are thoroughly stirred with a <u>broad</u> stirrer. This is especially important with matt paints. Apply a minimum of two full coats for protection.</p> <p><b>For Technical Enquiries or Material Safety Data Sheets. Contact Sales on 0191 4113146</b></p>	<p><b><u>Recommended Spreading Rate</u></b></p> <p>Up to 14m<sup>2</sup>/ltr</p> <p><b><u>Thinning</u></b></p> <p>Up to 5% White Spirit</p> <p><b><u>Drying Time</u></b></p> <p>Touch dry in 2-4 hours Recoatable after 16 hours under normal conditions (20°C 50% r/h).</p> <p><b><u>Cleaning</u></b></p> <p>Clean application equipment or spills with white spirit</p> <p><b><u>Limitations</u></b></p> <p>Treat any mould growth with Blackfriar Anti-Mould solution. Allow to fully dry prior to painting. Not suitable for use on quarry tiles.</p> <p><b><u>Environmental Info.</u></b></p> <p>Dangerous for the environment.</p> <p>Paint Product UN No. 1263.</p> <p><b>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</b></p>
--	---	---