

# **BLACKFRIAR PAINTS LTD**

## **TECHNICAL DATA SHEET**

### **BF091 Blackfriar Undercoat.**

Revision  
date:  
25/10/2010

<p><b><u>Product Information</u></b></p> <p><b><u>Description</u></b></p> <p>A high build undercoat with good obliteration properties.</p> <p><b><u>Usage/purpose</u></b></p> <p>Suitable for use as an 'intermediate coat ' between primer and finishing coats on most common substrates e.g. wood, plaster, metal etc.</p> <p><b><u>Characteristics</u></b></p> <p>A slightly structured coating with good levelling and covering properties.</p> <p><b><u>Finish</u></b></p> <p>Matt Finish</p> <p><b><u>Colour(s)</u></b></p> <p>White, Grey</p> <p><b><u>Packaging</u></b></p> <p>250ml, 500ml, 1litre, 2.5litre. Larger sizes may be available on request dependant on volume required</p> <p><b><u>Disclaimer;</u></b></p> <p>The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p><b><u>Technical Spec</u></b></p> <p><b><u>Composition</u></b></p> <p>Based on a blend of inorganic pigments with alkyd resin and linseed oil in low aromatic white spirits.</p> <p><b><u>VOC</u></b></p> <p><b>EU limit value for this product (cat A/d): 300 g/l (2010).</b> This product contains max 300 g/l VOC</p> <p><b><u>Performance</u></b></p> <p>For interior or exterior use on surfaces after thorough preparation. Not a finish. Requires overcoating.</p> <p><b><u>Surface Preparation</u></b></p> <p>Ensure the substrate to be painted is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease etc). Where necessary prime new and bare areas with appropriate Blackfriar Primer. Ensure all knots are sealed with Blackfriar Patent Knotting.</p> <p><b><u>Application Method</u></b></p> <p>Brush, Roller, Spray. Ensure products are thoroughly stirred with a broad stirrer. For best results apply two coats of undercoat before over-coating.</p> <p><b>For Technical Enquiries and Material Safety Data Sheets Telephone sales on 0191 4106611</b></p>	<p><b><u>Recommended Spreading Rate</u></b></p> <p>13m<sup>2</sup>/ltr</p> <p><b><u>Drying Time</u></b></p> <p>Touch dry in 2-4 hours Recoat after 16 hours under normal conditions (20°C 50% RH).</p> <p><b><u>Cleaning</u></b></p> <p>Clean application equipment or spills with white spirit or Blackfriar Brush Cleaner</p> <p><b><u>Limitations</u></b></p> <p>If used externally overcoat with an external quality finish.</p> <p><b><u>Environmental Info.</u></b></p> <p>Flammable</p> <p>Paint Product UN No. 1263.</p> <p><b>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</b></p>
--	---	---