

**BLACKFRIAR PAINTS LTD**  
**TECHNICAL DATA SHEET**  
BF046 **Blackfriar Interior Sealdamp.**

Revision date: 13/11/13
-------------------------------

<p><b><u>Product Information</u></b></p> <p><b><u>Description</u></b></p> <p>A clear coating which prevents damp patches from spoiling interior decoration.</p> <p><b><u>Usage/purpose</u></b></p> <p>Formulated for use on surfaces such as plaster, brickwork, cement and mortar.</p> <p><b><u>Characteristics</u></b></p> <p>Penetrates and seals surfaces against damp.</p> <p><b><u>Finish</u></b></p> <p>Glossy</p> <p><b><u>Colour(s)</u></b></p> <p>Clear with a slight yellow hue</p> <p><b><u>Packaging</u></b></p> <p>250ml, 500ml, 1litre, 2.5litre. Larger sizes may be available on request dependent on volume required</p> <p><b><u>Disclaimer;</u></b></p> <p>The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p><b><u>Technical Spec</u></b></p> <p><b><u>Composition</u></b></p> <p>Based on a high quality enamel oil.</p> <p><b><u>VOC</u></b></p> <p><b>EU limit value for this product (cat A/g): 350 g/l</b> This product contains max 350 g/L</p> <p><b><u>Performance</u></b></p> <p>For interior use. Can be over-coated with gloss, emulsion, textured finishes or wallpapers.</p> <p><b><u>Surface Preparation</u></b></p> <p>Always apply before the redecoration. Ensure the substrate to be painted is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease etc).</p> <p><b><u>Application Method</u></b></p> <p>Brush, Roller, Spray.</p> <p>Ensure products are <u>thoroughly</u> stirred with a broad stirrer. Apply at least two full coats for protection purposes.</p> <p><b><u>Recommended Spreading Rate</u></b></p> <p>Up to 14m<sup>2</sup>/L/coat depending on the substrate porosity.</p> <p><b>For Technical Enquiries, Material Safety Data Sheets Telephone 0191 4113146</b></p>	<p><b><u>Drying Time</u></b></p> <p>Touch dry in 2-4 hours Recoatable after 16 hours under normal conditions (20°C 50% RH).</p> <p><b><u>Cleaning</u></b></p> <p>Clean application equipment or spills with white spirit or Blackfriar Brush Cleaner</p> <p><b><u>Limitations</u></b></p> <p>May be applied on to damp substrates but this may cause the Blackfriar Sealdamp to take longer to dry. It is important to locate and cure the source of the damp prior to applying Sealdamp. Not suitable for use onto wallpaper. Will not cure efflorescence.</p> <p><b><u>Environmental Info.</u></b></p> <p>Dangerous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Flammable.</p> <p>Paint Product UN No. 1263.</p> <p><b>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</b></p>
--	--	--