

BLACKFRIAR
TECHNICAL DATA SHEET

BF0440001 BLACKFRIAR MULTI-SURFACE PRIMER
EXCELLENT ADHESION FOR MULTIPLE SURFACES ANTI-CORROSIVE
BLACKFRIAR MULTI-SURFACE PRIMER
Blackfriar Multi-Surface Primer has been specially formulated to prime multiple surfaces prior to further painting. It's ideal for hard and soft woods, chipboard, plywood, GRP, MDF, exterior UPVC, ceramic tiles, iron, steel, galvanised and non-ferrous metals (aluminium, brass, chrome, copper) and old plaster, and contains an anti-corrosive pigment to protect iron and steel.
PREPARATION Ensure the surface to be primed is clean, dry, sound and free from wax, grease and oil. If you are preparing wood or plaster, remove loose/ flaking paint, clean to a bare surface and sand smooth. Remove any fungal growth or mould with Blackfriar Concentrated Fungicidal Wash prior to application. Treat any knots or resinous wood with Blackfriar Patent Knotting and allow to dry before applying Blackfriar Multi-Surface Primer. If preparing iron and steel, remove any rust and mill scale with a wire brush, clean back to a bright surface, and prime immediately. Please note when applying to copper, the primer coat may turn blue – this colour will not be visible once a top coat is applied.
APPLICATION Stir thoroughly before use. Apply one coat of product by brush or roller except on ferrous metals and porous surfaces where two coats are required. For porous surfaces, dilute the first coat with 10% water. If applying two coats lightly sand the first coat prior to applying the second to remove any imperfections.
APPEARANCE White Matt Finish
COVERAGE RATE Up to 12m ² per litre per coat, 1-2 coats required (see APPLICATION). Coverage may vary depending on method, rate of application and roughness of surface.
DRYING TIME Touch dry in 1 hour. Apply a second coat after 4 hours if required. Drying times will be extended in low temperatures. Not recommended for use in damp conditions or if the temperature is below 10°C.
PACK SIZES 2.5L, 1L, 500ml & 250ml.
CLEAN UP Remove as much paint as possible from equipment before cleaning. Clean with warm water, rinse and dry thoroughly.
STORAGE Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.
HEALTH & SAFETY Keep out of the reach of children. Avoid contact with skin. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label. Dispose of this material and its container to hazardous or special waste collection point. EU limit value for this product (Cat A/i): 140 g/l. This product contains a maximum of 140 g/l VOC.
DISCLAIMER The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.
Blackfriar Paints – A Division of Tor Coatings, Portobello Industrial Estate, Birtley, Chester-le-Street, County Durham, DH3 2RE. For Technical Enquiries or Material Safety Data Sheets. Contact sales on 0191 410 6611.