

BLACKFRIAR PAINTS LTD

TECHNICAL DATA SHEET

BF024 Blackfriar Polyurethane Floor Varnish Clear

Revision
date:
08/01/2007

<u>Product Information</u>	<u>Technical Spec</u>	<u>Recommended Spreading Rate</u>
<p><u>Description</u></p> <p>A quality polyurethane floor varnish for interior use.</p> <p><u>Usage/purpose</u></p> <p>Specifically designed for floors but may be used on doors, joinery, furniture, wood panelling etc.</p> <p><u>Characteristics</u></p> <p>A high build clear finish.</p> <p><u>Finish</u></p> <p>Available in Gloss and Satin</p> <p><u>Colour(s)</u></p> <p>Clear (has a slight yellow hue)</p> <p><u>Packaging</u></p> <p>1litre, 2.5litre, 5litre. Larger sizes may be available on request dependant on volume required</p> <p><u>Disclaimer;</u> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p><u>Composition</u></p> <p>A blend of urethane and alkyd resins.</p> <p><u>Properties</u></p> <p>VOC Content: 478-482 g/litre.</p> <p><u>Performance</u></p> <p>An excellent hardwearing varnish – resists knocks, stains, dilute acids and alkalis. For interior use only.</p> <p><u>Surface Preparation</u></p> <p>Ensure the substrate to be varnished is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease, polish etc). If preparing a floor a previously wax polished floor <u>always</u> degrease prior to sanding. When applying to new wood thin the first coat with up to 10% white spirit as a sealer coat.</p> <p><u>Application Method</u></p> <p>Brush, Roller, Spray Ensure products are thoroughly stirred with a broad stirrer.</p> <p>For Technical Enquiries, Material Safety Data Sheets Telephone Sales on 0191 4106611</p>	<p>14m²/ltr</p> <p><u>Thinning</u></p> <p>Up to 10% with white spirit</p> <p><u>Drying Time</u></p> <p>Touch dry in 2-4 hours Recoat after 16 hours under normal conditions (20°C 50% r/h). NB. Due to hardness of this varnish, if left to dry in excess of 24 hours it must be rubbed down with fine abrasive paper and degreased prior to applying a further coat.</p> <p><u>Cleaning</u></p> <p>Clean application equipment or spills with white spirit or Blackfriar Brush Cleaner.</p> <p><u>Limitations</u></p> <p>For interior use only</p> <p><u>Environmental Info.</u></p> <p>Dangerous for the environment</p>
		<p>Paint Product UN No. 1263.</p> <p>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</p>