

BLACKFRIAR PAINTS LTD

TECHNICAL DATA SHEET

BF 062 Blackfriar Quick Drying Radiator Paint.

Revision
date:
08/01/2007

<u>Product Information</u>	<u>Technical Spec</u>	<u>Recommended Spreading Rate</u>
<p><u>Description</u></p> <p>A non-yellowing quick drying radiator paint.</p>	<p><u>Composition</u></p> <p>Based on a high quality acrylic emulsion and Titanium Dioxide.</p>	<p>13m²/ltr</p>
<p><u>Usage/purpose</u></p> <p>Suitable for use on oil or water filled radiators, pipework etc.</p>	<p><u>Properties</u></p> <p>VOC Content: 58 g/litre.</p>	<p><u>Thinning</u></p> <p>Up to 10% with water.</p>
<p><u>Characteristics</u></p> <p>A quick drying paint. Heat resistant to 150°C/300°F. Does not yellow like oil based paints.</p>	<p><u>Performance</u></p> <p>Heat resistant to 150°C Non Yellowing.</p>	<p><u>Drying Time</u></p> <p>Touch dry in 1-2 hours. After stoving allow to cool before applying a further coat.</p>
<p><u>Finish</u></p> <p>Semi Gloss</p>	<p><u>Surface Preparation</u></p> <p>Remove all signs of rust to a clean bright surface. Ensure the substrate to be painted is free from any surface contaminant likely to give adhesion problems (e.g. wax, grease etc). Where necessary prime new and bare areas with the appropriate Blackfriar Primer.</p>	<p><u>Cleaning</u></p> <p>Clean application equipment or spills with water.</p>
<p><u>Colour(s)</u></p> <p>Brilliant White</p>	<p><u>Application Method</u></p> <p>Brush, Roller, Spray Ensure product is <u>thoroughly</u> stirred with a broad stirrer. Apply at least two full coats. After each application allow to dry for one hour, then stove with radiator at full heat (70⁰C) for one hour to ensure thorough drying.</p>	<p><u>Limitations</u></p> <p>New/ bare metal must be primed. Do not apply in cold (below 5°C) or damp/humid conditions Protect paint film from water or steam for 2-3days after application.</p>
<p><u>Packaging</u></p> <p>250ml, 500ml. Larger sizes may be available on request dependent on volume required.</p>		<p><u>Environmental Info.</u></p> <p>Water-Based.</p>
<p><u>Disclaimer;</u></p> <p>The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.</p>	<p>For Technical Enquiries, Material Safety Data Sheets Telephone Sales on 0191 4106611</p>	<p>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</p>