### Review date: 12/11/13

# BLACKFRIAR TECHNICAL DATA SHEET

### BF029 Quick Drying Interior Floor Varnish Clear.

### Product Information

#### **Description**

Clear quick drying water based floor varnishes

#### **Usage/purpose**

Primarily designed for protection of floors. May also be used on doors, joinery, furniture, wood panelling etc

#### **Characteristics**

A smooth finish that brings out the natural beauty of wood. Low odour, quick drying, virtually colourless when dry.

#### **Finish**

Gloss or Satin

#### Colour(s)

Almost colourless

#### **Packaging**

1litre, 2.5litre, 5 litre.

#### Disclaimer;

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements

## Technical Spec Composition

Based on a high quality acrylic emulsion. Contains polyurethane.

#### **Properties**

VOC Content:

EU Limit (cat A/i); 140g/L This product contains max 140g/L

#### **Performance**

Hardwearing – resists knocks, boiling water, alcohol, stains and dilute acids and alkalis.

#### **Surface Preparation**

Ensure the substrate to be varnished is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease, polish etc). If preparing a floor which, has been previously waxed polished always degrease prior to sanding. When applying to new wood thin the first coat with up to 10% water.

## Application Method

Brush, Roller, Spray Ensure products are thoroughly stirred with a broad stirrer, especially important with Satin.

For Technical Enquiries or Material Safety Data Sheets, contact Sales on 0191 4113146

## **Recommended Spreading Rate**

Up to 14m<sup>2</sup>/L Apply 3-4 coats for optimum performance.

#### **Thinning**

Up to 10% water.

#### **Drying Time**

Touch dry in 1 hour Recoatable after 4 hours under normal conditions (20°C 50% r/h).

#### **Cleaning**

Clean application equipment or spills with water

#### **Limitations**

For interior use only.

#### **Environmental Info.**

Water-Based.

Tor Coatings Ltd.
Portobello Industrial Est,
Birtley
Chester-le Street
County Durham
DH3 2RE