

BLACKFRIAR PAINTS LTD

TECHNICAL DATA SHEET

BF082 Blackfriar Raw Linseed Oil

Revision
date:
09/01/2007

<p><u>Product Information</u></p> <p><u>Description</u></p> <p>A natural treatment for wood.</p> <p><u>Usage/purpose</u></p> <p>Suitable for use on oak beams, cricket bats, bean canes. Also used for softening putty and as a lubricant for French polishing. 'Feeds' wood.</p> <p><u>Characteristics</u></p> <p>An oily liquid with a characteristic odour</p> <p><u>Finish</u></p> <p>Does not leave a finish</p> <p><u>Colour(s)</u></p> <p>Clear with a slight yellow hue.</p> <p><u>Packaging</u></p> <p>250ml</p> <p><u>Disclaimer;</u> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.</p>	<p><u>Technical Spec</u></p> <p><u>Composition</u></p> <p>Raw linseed oil</p> <p><u>Properties</u></p> <p>VOC Content: EU Limit Value (CatA/e): 400g/L This product contains maximum 400g/L</p> <p><u>Performance</u></p> <p>Interior or exterior finish. NB. If used externally, will require very regular maintenance to continue to keep wood nourished.</p> <p><u>Surface Preparation</u></p> <p>Ensure the substrate to be oiled is sound and free from any surface contaminant When applying to new wood thin first coat with up to 10% white spirit or Blackfriar Genuine Turpentine.</p> <p><u>Application Method</u></p> <p>Ensure the Raw Linseed Oil is <u>thoroughly</u> shaken. Apply sparingly with a lint free rag. Ensure the oil is worked in to the wood. Remove any excess oil from the wood after allowing time for absorption.</p> <p>For Technical Enquiries, Material Safety Data Sheets Telephone 0191 4106611</p>	<p><u>Recommended Spreading Rate</u></p> <p>Up to 10m²/L/coat Dependant on absorbency of the wood.</p> <p><u>Thinning</u></p> <p>Up to 10% with white spirit or Blackfriar Genuine Turpentine.</p> <p><u>Drying Time</u></p> <p>Non-drying oil absorbs into the wood.</p> <p><u>Cleaning</u></p> <p>Clean application equipment or spills with white spirit or Blackfriar Brush cleaner</p> <p><u>Limitations</u></p> <p>When used outside finish must be maintained regularly (<u>at least</u> once a year). Rags used with this material are combustible. Destroy all rags after use by burning outside or lay cloths flat in single layers to dry out prior to disposal.</p> <p><u>Environmental Info.</u></p> <p>Dangerous for the environment</p> <p>Paint Product UN No. 1263.</p> <p>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</p>
--	--	---