

# **BLACKFRIAR PAINTS LTD**

## **TECHNICAL DATA SHEET**

### **BF047 Blackfriar Stabilising Solution**

Review date:  
27/02/07

<p><b><u>Product Information</u></b></p> <p><b><u>Description</u></b></p> <p>Clear quick drying water based sealer.</p> <p><b><u>Usage/purpose</u></b></p> <p>For interior and exterior use over weathered cement based paints or powdery surfaces such as old limewash or distemper.</p> <p><b><u>Characteristics</u></b></p> <p>Low odour, clear coating.</p> <p><b><u>Performance</u></b></p> <p>Binds powdery surfaces, deep penetrating.</p> <p><b><u>Finish</u></b></p> <p>Clear satin</p> <p><b><u>Colour(s)</u></b></p> <p>Almost colourless.</p> <p><b><u>Packaging</u></b></p> <p>500ml, 1l, Larger sizes may be available on request dependant on volume required.</p> <p><b><u>Disclaimer;</u></b></p> <p>The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p><b><u>Technical Spec</u></b></p> <p><b><u>Composition</u></b></p> <p>Based on an acrylic emulsion.</p> <p><b><u>Properties</u></b></p> <p>VOC Content: 5 g/l.</p> <p><b><u>Surface Preparation</u></b></p> <p>Ensure the substrate to be treated is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease, polish etc). Remove all loose and flaking material.</p> <p><b><u>Application Method</u></b></p> <p>Brush, Roller, Spray. Apply a generous even coat. On particularly porous or powdery surfaces a second coat may be required.</p> <p><b><u>Recommended Spreading Rate</u></b></p> <p>7 - 13m<sup>2</sup>/ltr depending on porosity of the surface.</p> <p><b>For Technical Enquiries, Material Safety Data Sheets, contact Sales on 0191 4106611.</b></p>	<p><b><u>Thinning</u></b></p> <p>Not required or recommended.</p> <p><b><u>Drying Time</u></b></p> <p>2-4 hours under normal conditions (20°C 50% r/h). Surface moisture content or damp weather may prolong the drying time. Allow to dry fully between coats or before decorating.</p> <p><b><u>Cleaning</u></b></p> <p>Clean application equipment or spills with water</p> <p><b><u>Limitations</u></b></p> <p>Do not apply at temperatures below 5° C and or damp/ humid conditions. Store in frost free conditions.</p> <p><b><u>Environmental Info.</u></b></p> <p>Water-Based.</p> <p><b>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</b></p>
---	---	---