

BLACKFRIAR

BF0761001 TEAK OIL
AN OIL FINISH FOR ENHANCING THE APPEARANCE OF TEAK AND SIMILAR HARD WOODS
INTERIOR / EXTERIOR USE ENHANCES THE APPEARANCE OF WOOD NOURISHES AND FEEDS WOOD REDUCES SURFACE SPLITTING
BLACKFRIAR TEAK OIL Blackfriar Teak Oil protects, revives and enhances the appearance of Teak and similar hardwoods. Ideal for hardwood furniture, doors and panelling. When used regularly it will reduce the risk of wood greying, weathering and surface splitting.
PREPARATION Ensure surface to be oiled is smooth, clean, dry and free of contamination. For surfaces previously treated with oils or waxes clean back the surface to bare timber with fine wire wool and white spirit, working along the grain. Previously painted or varnished surfaces should be stripped back to bare using Blackfriar Professional Paint and Varnish Remover. Any French polish on surfaces must also be completely removed.
APPLICATION Ensure the product is thoroughly shaken prior to use. Apply oil liberally by brush or rag. Leave for a few minutes for the oil to absorb into the wood then wipe off any surplus. Allow the oil to dry for 24 hours before using or recoating. When applying to new wood thin the first coat with 5% white spirit.
APPEARANCE Clear finish.
COVERAGE RATE Up to 14m ² /litre per coat. Dependent on porosity of wood.
DRYING TIME Touch dry in 6 - 8 hours. Recoat after 24 hours and within 3 days. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.
PACK SIZES 2.5L, 1L, 500ML, 250ML.
CLEAN UP Take extra care as application cloths and soiled cleaning rags may self ignite without warning. Lay cloths out flat in single layers to dry, or wash out thoroughly in warm soapy water before disposal. Remove as much product as possible from application equipment before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.
VOC EU limit value for this product (cat A/f): 700 g/l. This product contains max 700 g/l VOC
LIMITATIONS Do not apply in wet conditions or if the temperature is below 5°C. For best results apply a minimum of three coats leaving a minimum of 24 hours between coats.
DISCLAIMER The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.
Tor Coatings Ltd, Portobello Industrial Estate, Birtley, Chester-le-Street, County Durham, DH3 2RE. For Technical Enquiries or Material Safety Data Sheets. Contact sales on 0191 410 6611.