

# **BLACKFRIAR PAINTS LTD**

## **TECHNICAL DATA SHEET**

### **BF037 Blackfriar Priming Paint (White Wood).**

Review date:  
08/01/2007

<b><u>Product Information</u></b>	<b><u>Technical Spec</u></b>	<b><u>Thinning</u></b>
<b><u>Description</u></b>  A traditional oil based white primer.	<b><u>Composition</u></b>  A blend of alkyd resins and oils with Titanium Dioxide.	Up to 10% with white spirit
<b><u>Usage/purpose</u></b>  For priming new or old bare softwood.	<b><u>Properties</u></b>  VOC Content: 242 g/litre	<b><u>Drying Time</u></b>  Touch dry in 2-4 hours Recoat after 16 hours under normal conditions (20°C 50% r/h).
<b><u>Characteristics</u></b>  A liquid penetrating primer giving excellent adhesion to wood.	<b><u>Performance</u></b>  An excellent primer for softwoods both inside and out.	<b><u>Cleaning</u></b>  Clean application equipment or spills with white spirit or Blackfriar Brush Cleaner
<b><u>Finish</u></b>  Very slight sheen	<b><u>Surface Preparation</u></b>  Ensure the substrate to be painted is sound and free from any surface contaminant likely to give adhesion problems (e.g. wax, grease etc).	<b><u>Limitations</u></b>  Must be overcoated with a paint finish. Not recommended for hardwoods (use Blackfriar Aluminium Wood Primer) Seal all Knots With Blackfriar Patent Knotting.
<b><u>Colour(s)</u></b>  White	<b><u>Application Method</u></b>  Brush, Roller, Spray Ensure products are <u>thoroughly</u> stirred with a broad stirrer. Apply 1 or 2 coats brushing well into the grain	<b><u>Environmental Info.</u></b>  Dangerous for the environment
<b><u>Packaging</u></b>  250ml, 500ml, 1litre, 2.5litre, 5 litres. Larger sizes may be available on request dependant on volume required	<b><u>Recommended Spreading Rate</u></b>  13m <sup>2</sup> /ltr	Paint Product UN No. 1263.
<b><u>Disclaimer;</u></b> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.	<b>For Material Safety Data Sheets or technical enquiries contact Sales on 0191 4106611</b>	<b>Tor Coatings Ltd.</b> <b>Portobello Industrial Est,</b> <b>Birtley</b> <b>Chester-le Street</b> <b>County Durham</b> <b>DH3 2RE</b>