

## DESCRIPTION

Johnstone's Aqua Satin is an innovative, water based satin finish for use on interior and exterior wood and metal. It looks, feels and applies more like a traditional satin finish and is quicker drying and has a low odour. To achieve the best finish use over Johnstone's Aqua Water Based Undercoat.

## RECOMMENDED USES



Suitable for interior and exterior use.

## TYPE OF SUBSTRATE

Ideal for interior and exterior wood and metal.

## COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

## FINISH

Satin.

## VOLUME SOLID

41.9%

## COVERAGE



Johnstone's Aqua Satin will cover approximately 10-12 square metres per litre depending on the nature and porosity of the surface being painted.

## DRYING TIME\*



Recoat after 4-6 hours.

## TRANSPORTATION & STORAGE

Avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

## CLEANER

Clean water.

## VOC CONTENT

LOW VOC CONTENT 0.30-7.99%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 130g/l (2010). This product contains max 50g/l VOC.

## FILM THICKNESS

Wet: 91µm, dry: 38µm.

## KEY PROPERTIES

- Tough, Durable & Quick Drying.
- Low odour, Water Based Technology.
- Applies and finishes more like a solvent based satin finish.

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare wood with Johnstone's Aqua Undercoat. Prime all other bare surfaces with the appropriate Johnstone's primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Apply one full coat of Johnstone's Aqua Undercoat to all correctly prepared and primed surfaces before application of Johnstone's Aqua Satin. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory. For additional information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com)

## APPLICATION



Stir well before use. Easy to apply by brush. Avoid overspreading. Do not apply in temperatures below 10°C or externally when rain is imminent. For best results use a synthetic brush.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Safety datasheet available for professional user upon request.

## SIZES

1 Litre, 2.5 Litre, 5 Litre.