

DESCRIPTION

A pliolite® resin based paint specially formulated for application to damp interior wall surfaces. Can be left as a finish in its own right or as a damp proofing primer/sealer prior to over-painting with Johnstone's Anti-Mould Acrylic, or other Johnstone's decorative finish. It incorporates a water-reactive agent which takes care of residual surface moisture, but this does not remove the need to repair any structural faults which allow water to penetrate into the fabric of the wall.

Pliolite® is a registered trademark of Eliokem.

RECOMMENDED USES



Can be used over damp interior wall surfaces, either as a primer/sealer prior to overpainting or as a finish in its own right.

SPECIAL PROPERTIES

Incorporates a water-reactive agent which eliminates residual surface moisture.

COLOUR RANGE

White.

FINISH

Matt.

VOLUME SOLID

36%

COVERAGE



Johnstone's Damp Proof Paint will cover at the rate of approximately 4 square metres per litre. It is important to ensure that this total film thickness is achieved – do not overspread.

DRYING TIME



Recoat after 16–24 hours under normal drying conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

White Spirit.

VOC CONTENT

HIGH VOC CONTENT 25–50%.

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i): 500g/l (2010). This product contains max 500g/l VOC.

FILM THICKNESS

Wet: 250µm, dry: 90µm.

SIZE

5 Litre

PREPARATION

This paint should be applied preferably to unpainted masonry surfaces. However, if these have been previously painted, remove as much of the old paint as possible by thorough scraping and wire brushing. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Treat any mould or lichen with Johnstone's Sterilisation Wash before removing with a scraper or stiff brush, then treat surface again with Johnstone's Sterilisation Wash. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354354.

APPLICATION



Stir well before use. A thick film is necessary for maximum effectiveness. Brush application can be employed, in which case two coats are recommended to achieve the required film thickness, allowing 16–24 hours between coats. Follow with subsequent Johnstone's decorative finish, or leave as a finish in its own right.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- DANGER
- Flammable liquid and vapour.
- Causes serious eye damage.
- Causes skin irritation.
- May cause an allergic skin reaction.
- May cause respiratory irritation.
- Harmful to aquatic life with long lasting effects.
- Hazardous ingredients: Portland cement.
- Avoid release to the environment.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- Wear protective gloves/protective clothing/eye/face protection.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE or doctor/physician.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment.
- Store in a well-ventilated place. Keep cool.
- Store locked up.
- Keep container tightly closed.
- Safety data sheet available on request.