

DESCRIPTION

Johnstone's Flat Matt is a high quality dead matt emulsion suitable for all interior walls and ceilings, providing a completely flat finish with excellent opacity, coverage and application.

RECOMMENDED USES



Interior walls and ceilings

TYPE OF SUBSTRATE

Wood, metal and plaster. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork in internal situations.

COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

FINISH

Matt

VOLUME SOLID

27%

COVERAGE



Johnstone's Flat Matt will cover approximately 12-14 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 1-2 hours.
Recoat after 2-4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position. Protect from frost.

THINNER

Clean water.

VOC CONTENT

LOW VOC Content 0.3-7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 30g/l (2010).
This product contains max 30g/l VOC.

FILM THICKNESS

Wet: 90µm Dry: 24µm

KEY PROPERTIES

- Fashionable dead flat matt finish
- Wide colour offer
- Excellent opacity

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For additional information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces with a coat of Flat Matt thinned up to 10% with clean water. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents to a Waste Disposal Site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not breathe spray. Wear respiratory protection.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: wash with plenty of soap and water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Safety data sheet available on request.

SIZES

2.5 Litre, 5 Litre.