

DESCRIPTION

A solvent-borne, traditional matt finish formulated for interior use. Based on an alkyd resin it provides excellent obliteration and flow characteristics and produces a smooth even finish with excellent durability.

RECOMMENDED USES

Plaster and wood. Can also be used on metal, wallboards, concrete, cement rendering, brickwork and blockwork.

SPECIAL PROPERTIES

Suitable on a wide range of suitably primed substrates.

COLOUR RANGE

Brilliant White.

FINISH

Matt.

VOLUME SOLID

49%.

COVERAGE

Johnstone's Flat Oil Paint will cover at the rate of approximately 16–18 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME

Recoat after 16–24 hours under normal drying conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

White Spirit.

VOC CONTENT

HIGH VOC CONTENT 25–50%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 300g/l (2010).
This product contains max 300g/l VOC.

FILM THICKNESS

Wet: 80µm, dry: 40µm.

SIZE

2.5 Litre

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstones Specialist Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For additional information and free Johnstone's Trade datasheets, call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION

Stir well. Easy to apply by brush or roller.

CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- **WARNING**
- Flammable liquid and vapour.
- Contains 2-butanone oxime. May produce an allergic reaction.
- Safety data sheet available on request.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **IF ON SKIN:** Wash with plenty of water. Do not use solvent thinners or White Spirit.
- **IF SWALLOWED:** Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- Not recommended for interior use on large surface areas, or in confined spaces.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.