

### DESCRIPTION

Woodworks Floor Varnish has been specially formulated for use on all interior timber floors. It provides a tough, hardwearing, protective finish that enhances the natural beauty of the wood. This special formulation is ideal for 'heavy traffic' areas and resists heat, chemical spillage and scratching.

### AVAILABLE IN

2.5 litre and 5 litre sizes.

### COLOUR RANGE

Clear Gloss and Clear Satin.

### RECOMMENDED USES



Suitable for interior use.

### TYPES OF SUBSTRATE

Interior timber floors and cork tiles.

### COVERAGE



Approximately 17 square metres per litre depending on the nature and porosity of the surface being varnished.

### DRYING TIME



Recoat after 16–24 hours under normal conditions. Avoid heavy traffic until fully dry.

### TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.  
**STORE AWAY FROM HEAT AND FLAME.**

### THINNER

White Spirit.

### VOC CONTENT

HIGH VOC CONTENT 25-50%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution. EU limit value for this product (Cat A/i): 500g/l (2010). This product contains max 400g/l VOC.

### PREPARATION

Ensure all surfaces to be varnished are sound, clean, dry and free from dust, grease, polish or any other surface contaminant. Remove any flaking or cracked varnish. Sound, existing varnish should be rubbed down with fine waterproof abrasive paper, rinsed thoroughly and allowed to dry. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

### APPLICATION



Stir Floor Varnish thoroughly before use. Apply two or more coats of varnish evenly, by good quality brush along the wood grain as required. Do not overlap the brush strokes.

### CLEANING



Remove as much product as possible from brushes before cleaning. Clean brushes immediately after use with White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

### PRECAUTIONS

- Flammable liquid and vapour.
- Contains 2-butanone oxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.
- Safety data sheet available on request.