

DESCRIPTION

Johnstone's Microbarr Anti Bacterial Acrylic Eggshell is a high performance, tough acrylic resin based interior coating, formulated to assist in the fight against hospital acquired infections, caused by harmful bacteria. Formulated using Silver Ion technology, Johnstone's Microbarr is proven to actively inhibit MRSA and E-Coli over the painted surface.

RECOMMENDED USES



Developed using Silver Ion Technology to inhibit bacteria and provide a tough, washable finish. For interior use in areas of high traffic and when hygiene protection is required.

SPECIAL PROPERTIES

Tough, durable Eggshell formulated to assist in the fight against infections caused by harmful bacteria.

COLOUR RANGE

Brilliant White, Magnolia. Available in a range of colours via the Johnstone's tinting system.

FINISH

Eggshell.

VOLUME SOLID

36%

COVERAGE



Johnstones Microbarr Anti-Bacterial Acrylic Matt will cover approximately 12 square metres per litre depending on the nature and porosity of the surface. If more than one can of a colour is to be used in the same area, intermix before use.

DRYING TIME



Touch dry in 1-2 hours.
Recoat after 3-4 hours.

TRANSPORTATION & STORAGE

Avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Clean water.

VOC CONTENT

LOW VOC CONTENT 0.30-7.99%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 30g/l (2010).
This product contains max 30g/l VOC.

FILM THICKNESS

Wet: 83µm, dry: 30µm.

SIZE

5 Litre.

PREPARATION

All surfaces should be sound, clean, dry and free from grease. Remove any crazed or flaking paint. Rub down sound glossy surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a pre-coat of Johnstones Acrylic Primer Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory. Seal absorbent surfaces with a solution of up to 1 part water to 4 parts Anti-Bacterial Acrylic Matt. Prime bare timber and metal surfaces with an appropriate Johnstones primer. Allow radiators to cool before painting. For additional information and free Johnstones Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces with a coat of Anti-Bacterial Acrylic Eggshell thinned up to 10% with clean water. If more than one can of a colour is to be used in the same area, intermix before use.

CLEANING



Remove as much product as possible from equipment before cleaning. Clean immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty waste paint into drains or watercourses.

PRECAUTIONS

- Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one (EC no.247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no.220-239-6) (3:1), 1,2-benzisothiazol-3(2H)-one and othilinone (ISO). May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Safety data sheet available on request.