

DESCRIPTION

Opaque Wood Finish is a premium quality, low maintenance, alkyd resin based wood finish for interior and exterior use. It provides a satin, opaque, microporous finish which is water repellent and resists UV attack. Suitable for use on rough sawn and smooth planed timber surfaces.

AVAILABLE IN

2.5 litre and 5 litre sizes.

COLOUR RANGE

Clear; Light Oak; Jacobean Oak; Redwood; Mahogany; Ebony; Medium Oak; Walnut; Pine; Antique Pine; Rosewood; and Teak.

A Range of colours available in 2.5 litre and 5 litre only via the Johnstone's CMS2010 Tinting System.

RECOMMENDED USES



Suitable for exterior use.

TYPES OF SUBSTRATE

Garden furniture, trellis work, cladding, sheds, gates, fascias, fencing, rough sawn and smooth planed timber.

COVERAGE



Approximately 12 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Recoat after 16–24 hours under normal drying conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.

STORE AWAY FROM HEAT AND FLAME.

CLEANER

White Spirit.

VOC CONTENT

HIGH VOC CONTENT 25-50%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution. EU limit value for this product (Cat A/e): 400g/l (2010). This product contains max 400g/l VOC.

PREPARATION

Ensure all timber to be treated is sound, clean, dry (moisture content not more than 20%) and free from loose and flaking material. Pre-treat bare timber with a suitable clear timber preservative. Treat any mould or lichen with Sterilisation Wash as directed. Avoid inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION



Stir Opaque Wood Finish well before and during use. Apply using brush. Two coats are sufficient, however, a third will give added protection. Ensure all end grains are treated with each coat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

CLEANING



Remove as much product as possible from brushes before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Flammable liquid and vapour.
- Contains 2-butanone oxime. May produce an allergic reaction.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.
- Safety data sheet available on request.