

DESCRIPTION

Johnstone's Stormshield Quick Dry Stabilising Solution is a penetrating solution formulated for application to surfaces of a highly porous or friable nature. It provides a substrate suitable for further decoration with paints such as Johnstone's Stormshield Smooth Masonry, Stormshield Textured Masonry and Jontex High Build Masonry Finishes. The quick drying formula allows the masonry paint to be applied with minimum delay.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPE OF SUBSTRATE

Concrete, cement rendering, brick, stone, blockwork and pebble dash.

COLOUR RANGE

Clear (once dry).

FINISH

Not Applicable.

VOLUME SOLID

9%

COVERAGE



Approximately 6–10 square metres per litre depending on the nature and porosity of the surface.

DRYING TIME



A drying time of 2-4 hours should be allowed before applying Masonry paint.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

THINNER

Clean water.

VOC CONTENT

Minimal VOC content 0–0.29%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/h): 30g/l (2010).
This product contains max 3g/l VOC.

FILM THICKNESS

Wet: not applicable, dry: not applicable.

KEY PROPERTIES

- Quick drying and low odour
- Binds friable or chalking surfaces to produce a surface suitable for further decoration.
- Highly penetrative water-borne formulation.

PREPARATION

All surfaces to be treated should be clean, dry and free from loose and flaking material. Repair cracks and defective areas and treat fungal or algal growth with Fungicidal or Sterilisation Wash as directed. Wear a suitable face mask when creating dust.

Do not use Quick Dry Stabilising Solution on new/sound surfaces. Apply a thinned coat of Masonry Paint (see can for details).

For further advice contact Technical Advisory, on 01924 354354.

APPLICATION



Stir well before use. Apply one coat of Quick Dry Stabilising Primer liberally by brush, working the primer well into the surfaces. Do not apply under conditions less than 10°C or externally when rain is imminent.

CLEANING



Remove as much product as possible from the application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not breathe spray. Wear respiratory protection.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

SIZES

5 Litre.