

DESCRIPTION

Combining the benefits of water based technology with the best attributes of solvent based coatings, the formulation Quick Dry Opaque Wood Finish gives a long lasting, all weather, microporous, protective finish. Ideal for garden furniture and exterior woodwork on both rough sawn and smooth planed timber, it ensures most tasks can be completed in one day.

AVAILABLE IN

2.5 litre and 5 litre.

COLOUR RANGE

Clear; Light Oak; Jacobean Oak; Redwood; Mahogany; Ebony; Medium Oak; Walnut; Pine; Antique Pine; Rosewood; and Teak.

A Range of colours available in 2.5 litre and 5 litre via the Johnstone's CMS2010 Tinting System.

RECOMMENDED USES



Suitable for exterior use.

TYPES OF SUBSTRATE

Garden furniture, trellis work, gates, sheds, fencing, cladding, fascias, rough sawn and smooth planed timber.

COVERAGE



Approximately 12 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 2–4 hours.
Recoat after 4 hours.
Allow first coat to dry before recoating. Conditions of low temperature and high humidity will prolong drying time.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position. PROTECT FROM FROST.

THINNER

Water.

VOC CONTENT

LOW VOC CONTENT 0.30–7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution. EU limit value for this product (Cat A/e): 130g/l (2010). This product has max 80g/l VOC.

PREPARATION

Ensure all timber to be treated is sound, clean, dry and free from dust, grease, polish or any other surface contaminant. Treat any mould or lichen with a fungicidal wash as directed. Sand smooth natural planed wood and wipe clean with White Spirit to remove any natural oils or resins and allow to dry. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION



Stir Quick Dry Opaque Wood Finish thoroughly before and during use. Ensure gloves are worn during application to avoid staining of hands. Apply by brush working well into the timber along the grain. Usually one coat will be sufficient, unless on rough or badly cracked timber when two coats should be applied. The final colour achieved will depend on the colour and porosity of the timber and the number of coats applied.
Do not apply when the temperature is below 10°C or when rain is imminent.

CLEANING



Remove as much product as possible from brushes before cleaning. Clean brushes immediately after use with warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one (EC no.247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no.220-239-6) (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Safety data sheet available on request.