

**DESCRIPTION**

Johnstone's Ultra High Opacity Matt is a high opacity emulsion designed to achieve the appearance of a two coat application in just one coat. It is water based and easy to use and dries to a tough hard wearing matt finish.

**RECOMMENDED USES**

INTERIOR

Suitable for interior use.

**TYPE OF SUBSTRATE**

Interior walls and ceilings.

**COLOUR RANGE**

Over 7,000 colours are available via the Johnstone's Tinting System.

**FINISH**

Matt.

**VOLUME SOLID**

35%

**COVERAGE**

COVERAGE



Approximately 8 square metres per litre depending on the nature and porosity of the surface.

**DRYING TIME**

RECOAT



Touch dry in 2 hours.  
Recoat after 4 hours.

**TRANSPORTATION & STORAGE**

Avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

**THINNER**

Clean water.

**VOC CONTENT**

Low VOC content 0.3–7.99%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 30g/l (2010).  
This product contains max 30g/l VOC.

**FILM THICKNESS**

Wet: 100µm, dry: 31µm.

**KEY PROPERTIES**

- High opacity – designed to achieve the appearance of a two-coat application in just one coat.
- Minimum application time.
- Ease of application.

**PREPARATION**

Ensure the surface to be painted is clean, dry and free from grease. Remove any loose flaking or powdery material. Rub down glossy surfaces with fine waterproof abrasive paper and rinse thoroughly to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory, on 01924 354354.

**APPLICATION**

Stir well before use and apply by brush, roller or paint pad. For brush application, fully load the brush and apply liberally and evenly. Avoid overspreading. When using a medium pile roller or paint pad, apply generously and evenly. Do not apply in damp or cold conditions below 10°C.

**CLEANING**

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

**PRECAUTIONS**

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

**SIZES**

5 Litre.