

## Contract Matt

### DESCRIPTION

A high quality emulsion paint, specially formulated to provide a full-bodied, high opacity, matt finish to all interior walls and ceilings making it ideal for new work application. Suitable for interior use on new and aged plaster, wallboards, concrete, cement rendering, blockwork and brickwork.

### USES

Suitable for wall and ceiling surfaces in most normal interior situations. Ideal for use in schools, hotels, restaurants, canteens, food stores and bakeries, where its low odour qualities, combined with speed of drying enable the work to be completed with minimum disruption.

### RECOMMENDED USES

Interior.

### TYPE OF SUBSTRATE

Plaster and embossed wallcoverings. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork.

### COLOUR RANGE

Brilliant White and Magnolia.

### FINISH

Matt.

### COVERAGE

Approximately 13 square metres per litre depending on the nature and porosity of the surface being painted.

### DRYING TIME

Touch dry in 1-2 hours. Recoatable after 2-4 hours.

### TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position.

PROTECT FROM FROST.

### THINNER

Clean water.

### PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking materials. Prime bare surfaces with the appropriate Leyland Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

### APPLICATION INSTRUCTIONS

Stir well. Easy to apply by brush, roller or spray. Seal absorbent surfaces with a coat of Contract Matt thinned up to 10% with clean water. Do not apply in temperatures below 5°C. If more than one can of a colour is to be used in the same area, intermix before use.

### CLEANING

Remove as much product as possible from application equipment before washing. Replace lid firmly. Wash equipment immediately after use with warm soapy water. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

### PRECAUTIONS

#### PAINT PRODUCT

Ensure good ventilation during application and drying. Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.

When spraying do not breathe spray, wear suitable respiratory protective equipment.

Keep out of reach of children.

### PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

### VOC CONTENT

LOW VOC CONTENT 0.3-7.99%  
VOC's (Volatile Organic Compounds)  
contribute to atmospheric pollution.

Manufactured under a quality system approved by the BSI.

Issue Date: 03/02

Kalon Decorative Products, Huddersfield Road, Birstall, Batley, West Yorkshire. WF17 9XA.

Telephone: 01924 354000 Facsimile: 01924 354001