

Liberon Superior Decking Stain is a versatile product which gives a water and UV-resistant finish to most types of exposed timber.

The finish will form a protective barrier against weathering, sunlight and extreme temperatures from -10°C to +35°C.

2h

Drying time:
recoat

CHARACTERISTICS

- It is quick-drying and easy to apply with a paint roller or brush without wiping and smoothing.
- Anti-slip safety: according to standard XP CENTS 16165, barefoot.

24h

Drying time:
fully dry



BIOSOURCED FORMULA

- Product based on vegetable oils and modified bio-based resins.
- Formula tested to standard NF EN 16640.



Tool cleaning:
water



Tools:
brush, roller

1l
±12^{sqm}

PREPARATION

Ensure the surface is clean, dry and free from previous finishes and dust. Lightly sand new wood and clean old wood with Liberon Tough Deck Clean and Revive.

- **Hardwoods** : It is recommended to leave the wood exposed for up to 12 months before applying this product. This allows the grain in the wood to open and breathe and aids adhesion of the product.

APPLICATION

- Apply the product in temperatures between 12°C and 25°C in dry weather.
- Stir very well before use to mix all the ingredients in the tin.
- Ensure the weather conditions will be dry for 24h before application.

- Apply a not too thick coat of Superior Decking Stain with a paint brush or roller. Allow to dry for 2h then apply a second coat.

- Any unabsorbed product remaining on the surface should be evened out with a brush to avoid unsightly marks.

- Leave to dry for at least 24h before use.

- Risk of self-combustion. Wet with water any textiles or tools soiled with the product and dispose of them in a tightly closed container.

- Remove as much of the oil as possible from the tools after use. Do not dispose of residues and washing water/solvents in the sink, toilet, sewer, bin,... in order to avoid discharge into the environment.

THE SECRET OF LIBERON

- *For general maintenance, clean with water.*
- *During the next season, we recommend applying a further coat of Superior Decking Stain if necessary.*
- *Always replace the lid, otherwise the product can deteriorate.*
- *May not be suitable for some exotic hardwoods, test first on an inconspicuous area.*

METAL
recycles
forever

Contains biocidal products (preservatives): contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1); 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. P102 : Keep out of reach of children. P271 : Use only outdoors or in a well-ventilated area. P501 : Dispose of contents/container to a waste collection center (contact the local authority). EU limit value for this product (cat A/I) : 140g/L (2010). This product contains max 1g/L VOC. Do not allow to freeze. CAUTION: Risk of self-combustion. Wet with water any textiles or tools soiled with the product and dispose of them in a tightly closed container.



© BRITISH COATINGS FEDERATION LTD ALL RIGHTS RESERVED
5062413

SUBJECT TO DEPOSITING THIS EMPTY CAN AT THE WASTE DISPOSAL CENTRE.