

*Liberon Superior Protection Woodstain is specially designed to protect and decorate outdoor woods exposed to bad weather conditions and UV.*

*Its microporous formulation allows the wood to breathe.*

~ Made in the EU ~

3h

Drying time: recoat

12h

Drying time: fully dry



Tool cleaning: water



Tools: brush, roller, spray gun



SUBJECT TO DEPOSITING THIS EMPTY CAN AT THE WASTE DISPOSAL CENTRE.



5062421

### DESTINATION

This woodstain is designed for :

- All exterior & interior vertical woodwork: cladding, doors, windows, gates, pergolas, fences, beams ...
- For most types of European and exotic woods, new or old (oak, softwood, larch, douglas fir, red cedar ...).
- Can be applied over most woodstains.

8

YEAR GUARANTEE

The 8 year guarantee applies for :

- New wood or renovation of common species when product is applied according to preparation and application instructions.
- EXPOSURE : Only vertical surfaces. For South and South-West exposure, apply 3 coats.
- The guarantee is limited to refunding of the product (presentation of the receipt and the tin) and concerns only the appearance of the woodstain.



### PREPARATION

The wood to be stained must be clean, dry, in good condition and not greasy. Sand corners and edges to round them slightly.

- **BARE OR REFURBISHED WOOD** : Sand with sandpaper to obtain a smooth surface and remove dust. Apply a suitable wood treatment product.
- **EXOTIC WOODS, OAK, CHESTNUT...** : Dilute the 1st coat with 10% water and apply a second non-diluted coat. On greasy woods, degrease the surface with acetone.
- **STAINED WOODS** : Brush to remove any loose or flaking finishes. Use sandpaper to obtain a smooth surface and remove dust.

### APPLICATION

Ideal application conditions are between 12° and 25°C, in dry, wind-free weather.

- Stir the product well before and during use using a wide stirrer.
  - Apply in 2 coats. For a spray application, dilute with 10% water.
- Remove as much of the woodstain as possible from the tools after use. Do not dispose of residues and washing water/solvents in the sink, toilet, sewer, bin,... in order to avoid discharge into the environment.

### THE SECRET OF LIBERON

- *Do not apply to thermo-heated, thermo-treated or acidic woods.*
- *For bright colours on new or exposed woods, it may be necessary to apply a 3rd coat.*
- *The clear shade is recommended only for maintenance on previously stained and tinted woods or to dilute other colour shades.*
- *Results may vary according to wood species. Always test product on a small or inconspicuous area for colour, compatibility and end result.*

Contains biocidal products (preservatives): contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1); 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. P102 : Keep out of reach of children. P271 : Use only outdoors or in a well-ventilated area. P501 : Dispose of contents/container to a waste collection center (contact the local authority). EU limit value for this product (cat A/e) : 130g/L (2010). This product contains max 4g/L VOC. Do not allow to freeze.

0.75L  
±9<sup>sqm</sup>