

**DOES
EXACTLY
WHAT IT
SAYS ON
THE TIN***

**Ronseal Promise, if you do exactly what it says on the tin,
this product will do exactly what it says on the tin.**

Ronseal 5 Year Woodstain

Ronseal 5 Year Woodstain is a superior quality finish which colours and enhances all smooth planed exterior wood and joinery, whilst providing long lasting weatherproof protection. The unique formula utilises water-based resin and wax technologies and micro-fine iron oxide pigments to ensure superior water repellency, UV resistance and therefore, guaranteed protection from all the elements. Ronseal 5 Year Woodstain is a flexible, medium build finish, guaranteed to last 5 years and its performance is independently certified by the British Board of Agrément (Certificate No. 96/3303).

Durable weather protection:

Ronseal 5 Year Woodstain is specially formulated to provide a durable, long lasting finish. Micro-fine iron oxide pigments give excellent clarity and colour, allowing the natural wood grain to show through. These high quality pigments provide superior U.V. resistance so the colour lasts for longer. The highly water repellent coating prevents excess water from entering the wood, while the microporous formula allows trapped moisture to evaporate, protecting against cracking, peeling and blistering. The formula also contains a film fungicide which inhibits surface mould growth.

Water-based formula:

Ronseal 5 Year Woodstain utilises water-based technology; it out-performs conventional woodstains – repelling water to protect the wood, it is quick drying – rainproof in just 1 hour, and clean up is easy – brushes wash out in water.

5 YEARS GUARANTEED

Ronseal 5 Year Woodstain is guaranteed to last. Ronseal will refund the original retail price, if the finish blisters, chalks or the colour fades within 5 years of being applied to bare, vertical wood or previously stained wood in good condition.

Usage Areas:	All smooth planed exterior timber, softwood & hardwood – Doors, window frames, cladding, soffits & fascias etc. Not suitable for decking.
Compatibility:	Suitable for use on bare wood or over existing solvent or water-based woodstains.
Finish:	High satin sheen.
Coverage:	Up to 20 square metres per litre. 750ml sufficient for 12-15 square metres per coat.
Dry Times:	Touch dry in 1 hour. Recoat in 4 hours.
Clean Up:	Brushes wash out in water and detergent.

Preparation:

No basecoats, no primers, Ronseal 5 Year Woodstain is all that is required to protect and decorate exterior wood. Make sure wood is clean and dry. Lightly sand to remove any loose wood fibres and wipe off any dirt, dust and grease with white spirit. Previously stained or weathered wood should be sanded, then washed with white spirit and allowed to dry. Avoid inhalation of dust, wear a suitable face mask when sanding. Other finishes such as varnish or paint must be completely removed before application. For the best possible finish use a good quality brush designed for the application of water-based finishes. Shade label indicates approximate colour only. Always test for colour on a small inconspicuous area.

Application:

Stir well before and during use. Apply even coats finishing in the direction of the wood grain. Apply 3 coats allowing 4 hours between coats. Lightly sand before final coat. In warm and dry conditions, for best results dilute the first coat with up to 25% water. Do not apply in direct sunlight. Weathered wood may reduce coverage rate. Coverage varies with the absorbency of the wood. Remove as much product as possible from application equipment before cleaning. Clean brushes immediately with detergent and water. Do not empty product into drains or watercourses. Some local authorities have special facilities for disposal of waste coatings.

Maintenance:

Once applied, Ronseal 5 Year Woodstain can be easily maintained by applying one further coat every 5 years. On certain softwoods and horizontal or very exposed surfaces more frequent treatment may be necessary.

IMPORTANT:

Special precautions should be taken during surface preparation of pre 1960's painted surfaces over wood and metal as they may contain harmful lead. For further information please contact Ronseal Technical Services. To avoid the risk of spillage always store and transport in a secure and upright position.

Guarantee compliance:

Ronseal 5 Year Woodstain should be applied in accordance with the instructions on the can. Any failure caused by the breakdown of the previous coating is not covered by this guarantee. Proof of purchase, showing where and when purchased, is required. This does not affect your statutory rights.

RONSEAL 5 YEAR WOODSTAIN

Use only in well ventilated areas. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. Keep out of reach of children. Protect from frost – do not apply at temperatures below 10°C or in high humidity.

EU limit value for this product (cat A/e): 150g/l (2007)/ 130g/l (2010). This product contains max 90g/l VOC.

For further advice please contact:

Ronseal Technical Services, Tel: 0114 240 9469

Ronseal Ltd, Thorncliffe Park, Chappeltown, Sheffield, S35 2YP

Tel: 0114 246 7171

Fax: 0114 245 5629

enquiry@ronseal.co.uk

www.ronseal.co.uk



750ml e

Ronseal and Ronseal Does Exactly What It Says On The Tin are registered trademarks of the Sherwin-Williams company. ©2010 Made in Great Britain.

