Strong stripping power on all types of decking.

Using the latest technological innovation Ronseal Decking Stripper has been specially formulated to remove all decking coatings such as stains and oils.

Effective in 2 hours, not only does it remove existing or flaking coatings, it provides excellent reviving properties leaving your deck looking like new and ready to be re-finished.

Usage Areas	Smooth or ridged hardwood and softwood decking.
Compatibility	Treated decking where the coating has started to weather.
Coverage	This 2.5L tin is sufficient to cover 6m^2 with 2 applications.
Clean Up	Clean tools in warm water and detergent.

Decking Stripper demo video

Scan with your smartphone or visit ronseal.com to see how it's done.

Preparation

Ronseal Decking Stripper can be applied to dry or damp wood. There must be no standing water on the deck as this will reduce the stripping power. Ensure the deck is free from surface debris. Do not apply in temperatures above 25°C or below 10°C. Lower temperatures will reduce effectiveness. Do not apply Decking Stripper in direct sunlight or to a hot surface otherwise it will dry out too quickly. Not suitable for use on new or untreated wood. To restore a grey, weathered deck back to its natural appearance, use Ronseal Decking Restorer.

Application

1. Wear suitable gloves. Ensure surrounding areas are well protected.
2. Shake thoroughly before pouring into a suitable metal or plastic container. Stir before and during use. Apply Ronseal Decking Stripper in sections that you can complete within 10 minutes, i.e. 2/3 boards, using a bristle brush or roller. Do not walk on the deck once the Stripper has been applied – ensure you leave an area free of product to walk on.
3. Apply the first coat of Decking Stripper and leave for an hour. Re-apply with a second coat and leave for another hour. Keep the surface wet with Stripper while it is working – do not allow it to dry out during this time as this will reduce the Stripper's effectiveness. If the Stripper begins to dry, re-apply product.
4. 1 hour after second coat is applied scrub the surface of a small test section with a stiff bristled deck brush while the Stripper is still wet to ensure the coating has been removed effectively. If not leave for a further 30 minutes and retest.
5. Once the coating has been removed effectively add a small amount of water to the surface and scrub the treated area to remove debris. Clean with a pressure washer paying particular attention to the grooves. If a pressure washer is not available rinse with a hose whilst scrubbing with a stiff bristled deck brush. Ensure all residues are washed away.

For stubborn areas re-treat as necessary. Allow the wood to dry thoroughly (usually 2 days) before re-coating with a Ronseal Decking finish: Decking Stain for durable colour and protection or Decking Oil for natural colour and nourishment.

Clean up

Remove as much product as possible from brushes before cleaning. Clean brushes with water and detergent. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings.

5 010214 867066

C00639

2.5 litre ℮

Ronseal Ltd., Chapeltown,
Sheffield S35 2YP
Tel: 0114 246 7171
Email: enquiry@ronseal.co.uk

Ronseal and Ronseal Does Exactly What it Says on the Tin are registered trademarks of The Sherwin-Williams Company. © 2012

Ronseal Decking Stripper

Highly flammable. Irritating to eyes.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Keep out of the reach of children.

Keep container in a well-ventilated place.

Keep away from sources of ignition – No smoking.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Wear suitable gloves.

If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas.

Dispose of this material and its container to a hazardous or special waste collection point.

If swallowed, rinse mouth with water (only if the person is conscious).

Avoid contact with skin and eyes.

Highly Flammable

IRRITANT

© VERY HIGH VOC CONTENT MORE THAN 50%
VOCs. (Volatile Organic Compounds) contribute to atmospheric pollution.
PROTECTED, USED UNDER LICENCE.

Does exactly what it says on the tin® Does exactly what it says on the tin® Does exactly what it says on the tin®