



## SAFETY DATA SHEET

### Sadolin Stainable Wood Filler Activator

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

##### **1.1. Product identifier**

Product name                      Sadolin Stainable Wood Filler Activator  
 Product No.                        6006336 - CLP

##### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

Identified uses                      For filling holes and cracks in wood. Applied by spatula or palette knife. See container for details. This product is a two pack system and both parts must be mixed in accordance with the manufacturers instructions.  
 Uses advised against              Any other than described above.

##### **1.3. Details of the supplier of the safety data sheet**

Supplier                              Sadolin Woodcare  
    Crown Paints  
    Crown House  
    Hollins Rd  
    Darwen  
    Lancs, BB3 0BG  
    Tel: 01254 704951  
    Fax: 01254 702678  
    sadolin.co.uk  
 Contact Person                      Product SHE Information Manager

##### **1.4. Emergency telephone number**

Tel: 01254 704951 (24hrs)

#### SECTION 2: HAZARDS IDENTIFICATION

##### **2.1. Classification of the substance or mixture**

Classification (1999/45/EEC)      Xi;R36. R43. O;R7.  
 Human health  
 Inhalation of organic solvent vapours may be hazardous to health.  
 Physical and Chemical Hazards  
 The oxidising ingredient in this preparation is stabilised (contained in phlegmatizer).

##### **2.2. Label elements**

Contains                              BENZOYL PEROXIDE  
 Labelling



Irritant



Oxidising

##### Risk Phrases

R7	May cause fire.
R36	Irritating to eyes.
R43	May cause sensitisation by skin contact.

##### Safety Phrases

S2	Keep out of the reach of children.
S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S46	If swallowed, seek medical advice immediately and show this container or label.
S56	Dispose of this material and its container to hazardous or special waste collection point.

# Sadolin Stainable Wood Filler Activator

S64

If swallowed, rinse mouth with water (only if the person is conscious).

## 2.3. Other hazards

This product does not contain any PBT or vPvB substances.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

2-Ethylhexyl benzoate	10-30%
CAS-No.: 5444-75-7	EC No.: 226-641-8
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) R53.
BENZOYL PEROXIDE	30-60%
CAS-No.: 94-36-0	EC No.: 202-327-6
Classification (EC 1272/2008) Org. Perox. B - H241 Eye Irrit. 2 - H319 Skin Sens. 1 - H317	Classification (67/548/EEC) E;R3 O;R7 Xi;R36 R43
Oxirane methylmonobutyl ether	1-5%
CAS-No.: 9038-95-3	EC No.:
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Xn;R22. Xi;R36/38.
Zinc distearate	5-10%
CAS-No.: 557-05-1	EC No.: 209-151-9
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Xn;R22. Xi;R36/38.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### Composition Comments

Strong exothermic polymerisation may occur if the product comes into contact with heat, free radical formers and peroxides.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

#### Inhalation

Remove to fresh air, keep the patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in a prone position with head to the side (recovery position) and seek medical advice.

#### Ingestion

If accidentally swallowed obtain immediate medical advice. Show this safety data sheet. Keep at rest. Do not induce vomiting. If conscious give milk or water to drink.

#### Skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do not use solvents or thinners.

# Sadolin Stainable Wood Filler Activator

Eye contact

Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.

## **4.2. Most important symptoms and effects, both acute and delayed**

General information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure.

Inhalation.

Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion

May cause discomfort if swallowed. Nausea, vomiting. Diarrhoea.

Skin contact

Prolonged contact may cause redness, irritation and dry skin.

Eye contact

Irritation of eyes and mucous membranes.

## **4.3. Indication of any immediate medical attention and special treatment needed**

Consult safety data sheet.

## **SECTION 5: FIREFIGHTING MEASURES**

### **5.1. Extinguishing media**

Extinguishing media

Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

### **5.2. Special hazards arising from the substance or mixture**

Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

Unusual Fire & Explosion Hazards

No unusual fire or explosion hazards noted.

Specific hazards

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Nitrous gases (NO<sub>x</sub>).

### **5.3. Advice for firefighters**

Special Fire Fighting Procedures

Keep up-wind to avoid fumes. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective clothing as described in Section 8 of this safety data sheet. Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area. Take precautionary measures against static discharges. Do not smoke, use open fire or other sources of ignition. Do not breathe vapour. Eye contact MUST be prevented by means of suitable personal protection equipment.

### **6.2. Environmental precautions**

Do not discharge onto the ground or into water courses. Do not allow ANY environmental contamination. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

### **6.3. Methods and material for containment and cleaning up**

If leakage cannot be stopped, evacuate area. Clean-up personnel should use respiratory and/or liquid contact protection. Wash thoroughly after dealing with a spillage. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb spillage with non-combustible, absorbent material. Transfer to a container for disposal. Flush area with plenty of water.

### **6.4. Reference to other sections**

For personal protection, see section 8. For waste disposal, see section 13.

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

## Sadolin Stainable Wood Filler Activator

Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Avoid contact with skin and eyes. Static electricity and formation of sparks must be prevented. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product. Observe good chemical hygiene practices. Do not use in confined spaces without adequate ventilation and/or respirator. Provide good ventilation. Container must be kept tightly closed.

### **7.2. Conditions for safe storage, including any incompatibilities**

Keep away from heat, sparks and open flame. Keep containers tightly closed. Keep away from food, drink and animal feeding stuffs. Flammable/combustible - Keep away from oxidisers, heat and flames. Keep in original container. Store away from: Acids. Alkalis.

Storage Class

The storage of this product is not subject to any statutory requirements.

### **7.3. Specific end use(s)**

Usage Description

Use product only in accordance with methods listed in section 1.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### **8.1. Control parameters**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
BENZOYL PEROXIDE	WEL		5 mg/m <sup>3</sup>			

WEL = Workplace Exposure Limit.

Ingredient Comments

LT = Long term exposure limit. ST = Short term exposure limit. TWA = Time weighted average. Ppm = Parts per million Mgm-3 = Milligrams per cubic metre. Sk = Indicates a risk of absorption through skin.

### **8.2. Exposure controls**

Protective equipment



Process conditions

Provide eyewash, quick drench.

Engineering measures

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided. At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used. Check that mask fits tight and change filter regularly.

Hand protection

Protective gloves must be used if there is a risk of direct contact or splash. Gloves of nitrile rubber, PVA or Viton are recommended.

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

Other Protection

Wear appropriate clothing to prevent any possibility of skin contact. Provide eyewash station.

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet.

Skin protection

Wear apron or protective clothing in case of splashes.

Environmental Exposure Controls

See section 12.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### **9.1. Information on basic physical and chemical properties**

Appearance	Viscous liquid.
Colour	White / off-white.
Odour	Characteristic.
Solubility	Immiscible with water

## Sadolin Stainable Wood Filler Activator

Initial boiling point and boiling range

Not determined.

Bulk Density 1.15 kg/l

Vapour density (air=1) >1

Vapour pressure

Not determined.

Viscosity 20 dPa.s @ 23 °C

Flash point Not self igniting CC (Closed cup).

Auto Ignition Temperature (°C)

Not determined.

Flammability Limit - Lower(%)

Not determined.

Flammability Limit - Upper(%)

Not determined.

### **9.2. Other information**

## **SECTION 10: STABILITY AND REACTIVITY**

### **10.1. Reactivity**

Rapid decomposition will occur if the product is heated. No decomposition will occur if used/ stored according to the manufacturers instructions.

### **10.2. Chemical stability**

Stable under normal temperature conditions and recommended use.

### **10.3. Possibility of hazardous reactions**

Self accelerated decomposition above 60°C.

### **10.4. Conditions to avoid**

Protect from frost, heat and sunlight.

### **10.5. Incompatible materials**

Materials To Avoid

Dirt, rust, concentrated acids, alkalis and accelerators (eg heavy metal compounds and amines).

### **10.6. Hazardous decomposition products**

None at ambient temperatures. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

### **11.1. Information on toxicological effects**

General information

Contains small amounts of organic solvents. Extensive use of the product in areas with inadequate ventilation may result in hazardous vapour concentrations.

Inhalation

When working extensively on big surfaces in small and badly ventilated rooms, vapours may develop in concentrations which may cause malaise such as headache, dizziness and nausea.

Ingestion

Nausea, vomiting. Headache. Diarrhoea.

Skin contact

May cause defatting of the skin, but is not an irritant. Repeated exposure may cause skin dryness or cracking. The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals after repeated contact.

Eye contact

May cause temporary eye irritation.

## **SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicity

There are no data on the ecotoxicity of this product. The product is not expected to be hazardous to the environment. The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

## Sadolin Stainable Wood Filler Activator

### **12.1. Toxicity**

Do not allow to enter drains, sewers or watercourses.

### **12.2. Persistence and degradability**

The product is not expected to be biodegradable.

### **12.3. Bioaccumulative potential**

Bioaccumulative potential

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

### **12.4. Mobility in soil**

Mobility:

Not considered mobile.

### **12.5. Results of PBT and vPvB assessment**

This product does not contain any PBT or vPvB substances.

### **12.6. Other adverse effects**

Not determined.

## SECTION 13: DISPOSAL CONSIDERATIONS

General information

When this product, in its liquid state, as supplied or skinned, becomes a waste, it is categorised as hazardous waste, with code 08 01 11 (list of wastes). Part used containers, not drained and/ or rigorously scraped out and containing dried residues of the supplied product, are categorised as non-hazardous waste, with code 08 01 12 (list of wastes). Used containers, drained and/ or rigorously scraped out and containing dried residues of the supplied product, are categorised as non-hazardous waste, with code 15 01 02 or 15 01 04 (list of wastes). If mixed with other wastes, the above waste code may not be applicable.

### **13.1. Waste treatment methods**

Do not allow runoff to sewer, waterway or ground. Dispose of waste and residues in accordance with local authority requirements.

Waste Class

Waste product 08 01 11 Used packaging containing only dried residues 15 01 02

## SECTION 14: TRANSPORT INFORMATION

General

This product is always supplied as a 2 pack product consisting of activator and base resin. The transport labelling on the product will reflect this.

### **14.1. UN number**

UN No. (ADR/RID/ADN) 3107

UN No. (IMDG) 3107

UN No. (ICAO) 3107

### **14.2. UN proper shipping name**

Proper Shipping Name ORGANIC PEROXIDE TYPE E, LIQUID (DIBENZOYL PEROXIDE)

### **14.3. Transport hazard class(es)**

ADR/RID/ADN Class 5.2

ADR/RID/ADN Class Class 5.2: Organic peroxides.

ADR Label No. 5.2

IMDG Class 5.2

ICAO Class/Division 5.2

Transport Labels

## Sadolin Stainable Wood Filler Activator



### **14.4. Packing group**

Not applicable.

### **14.5. Environmental hazards**

Environmentally Hazardous Substance/Marine Pollutant

No.

### **14.6. Special precautions for user**

EMS F-J, S-R

Emergency Action Code 2W

Tunnel Restriction Code (D)

### **14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

## **SECTION 15: REGULATORY INFORMATION**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### Uk Regulatory References

The products are classified and supplied in accordance with the Chemicals (Hazard Information Packaging for supply) regulations (CHIP). The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks as required by other health and safety legislation. The provision of the Health and Safety at Work Act and the Control of Substances Hazardous to Health regulations apply to the use of this product at work.

Approved Code Of Practice

Approved classification and labelling guide (Sixth edition) The compilation of safety data sheets (Third edition)

Guidance Notes

Workplace Exposure Limits EH40. Storage of Flammable Liquids in Containers, HS(G)51 Storage of Packaged Dangerous Substances, HS(G)71

EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Classification, labelling and packaging of substances and mixtures 1272/2008EC

National Regulations

The Control Of Substances Hazardous to Health regulations (as amended) The Manual Handling Operations regulations (as amended) The Environmental Protection (Duty of Care) regulations (as amended) The Chemicals (Hazard Information and Packaging) for supply regulations (as amended) The Health and Safety at Work act 1974 (as amended)

### **15.2. Chemical Safety Assessment**

No chemical safety assessment has been carried out.

## **SECTION 16: OTHER INFORMATION**

#### General information

The information contained in this safety data sheet is provided in accordance with the requirements of the regulations. The product should not be used for purposes other than those shown in section 1 without first referring to the supplier and obtaining written handling instruction. As the specific conditions of use of the product are outside the suppliers control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

Revision Comments

This information is provided in a revised format to that previously produced.

Issued By Product SHE Information Manager

Revision Date 22/11/12

SDS No. Revision 4

## Sadolin Stainable Wood Filler Activator

### Risk Phrases In Full

R3	Extreme risk of explosion by shock, friction, fire or other sources of ignition.
R22	Harmful if swallowed.
R36/38	Irritating to eyes and skin.
R36	Irritating to eyes.
R7	May cause fire.
R53	May cause long-term adverse effects in the aquatic environment.
R43	May cause sensitisation by skin contact.

### Hazard Statements In Full

H319	Causes serious eye irritation.
H241	Heating may cause a fire or explosion.
H242	Heating may cause a fire.
H317	May cause an allergic skin reaction.

### Disclaimer

The information provided in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health and safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.